




Pan-Ty® Cable Ties – Nylon 6.6

- For indoor use
- Versatile cable ties can be used in countless applications
- One-piece construction for consistent performance and reliability
- Among the lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation
- A variety of materials and colors available for specific applications
- UL Listed for use in plenum or air handling spaces per NEC except PLT.6SM and PLT5H/6H/8H/13H



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N			

Subminiature Cross Section

PLT.6SM-C	2.8	71	0.070	1.8	0.030	0.8	0.60	15	8	36	GTS-E, PTS	100	1000
-----------	-----	----	-------	-----	-------	-----	------	----	---	----	------------	-----	------

Miniature Cross Section – Plenum Rated

PLT.7M-C	3.1	79	0.090	2.3	0.032	0.8	0.68	17	18	80	GTS-E, GS2B-E, PTS, PPTS, STS2	100	1000
PLT1M-C	3.9	99	0.098	2.5	0.043	1.1	0.87	22					
PLT1.5M-C	5.6	142	0.098	2.5	0.043	1.1	1.25	32	18	80			
PLT2M-C	8.0	203	0.098	2.5	0.043	1.1	2.00	51					

Intermediate Cross Section – Plenum Rated

PLT1.5I-C	5.6	142	0.142	3.6	0.045	1.1	1.38	35	40	178	GTS-E, GS2B-E, PTS, PPTS, STS2	100	1000
PLT2I-C	8.0	203	0.142	3.6	0.045	1.1	2.00	51					
PLT2.5I-C	9.7	246	0.145	3.7	0.052	1.3	2.50	64					
PLT3I-C	11.4	290	0.145	3.7	0.052	1.3	3.00	76	40	178			
PLT4I-C	14.5	368	0.145	3.7	0.052	1.3	4.00	102					

Standard Cross Section – Plenum Rated UL TYPE 2S Rated

PLT1S-C	4.8	122	0.190	4.8	0.052	1.3	1.00	25	50	222	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2	100	1000
PLT1.5S-C	6.2	157	0.190	4.8	0.052	1.3	1.50	38					
PLT2S-C	7.4	188	0.190	4.8	0.052	1.3	1.88	48					
PLT2.5S-C	9.8	249	0.190	4.8	0.052	1.3	2.50	64	50	222			
PLT3S-C	11.5	292	0.190	4.8	0.052	1.3	3.00	76					
PLT4S-C	14.5	368	0.190	4.8	0.052	1.3	4.00	102					
PLT4.5S-C	15.5	394	0.190	4.8	0.052	1.3	4.50	114	50	222			
PLT5S-C	17.5	445	0.190	4.8	0.052	1.3	5.00	127					

Light-Heavy Cross Section (Straight Tip) – Plenum Rated

PLT2H-L	8.1	206	0.300	7.6	0.075	1.9	2.00	51	120	534	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	50	500
PLT2.5H-L	9.8	251	0.300	7.6	0.075	1.9	2.50	64					
PLT3H-L	11.4	290	0.300	7.6	0.075	1.9	3.00	76					
PLT4H-L	14.5	368	0.300	7.6	0.075	1.9	4.00	102					
PLT6LH-L	21.9	556	0.300	7.6	0.075	1.9	6.00	152	120	534			
PLT7LH-L	24.7	627	0.300	7.6	0.075	1.9	7.00	178					
PLT8LH-L	27.6	701	0.300	7.6	0.075	1.9	8.00	203					
PLT9LH-L*	30.5	775	0.300	7.6	0.075	1.9	9.00	229					
PLT10LH-L*	34.3	871	0.300	7.6	0.075	1.9	10.31	262	120	534			

Heavy Cross Section (Straight Tip)


PLT5H-L*	17.7	450	0.350	8.9	0.078	2.0	5.00	127	175	778	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	50	500
PLT6H-L*	20.9	530	0.350	8.9	0.078	2.0	6.00	152					
PLT8H-L*	30.6	779	0.350	8.9	0.078	2.0	9.00	229					
PLT13H-Q*	43.3	1100	0.350	8.9	0.078	2.0	13.00	330	175	778			

*UL Listed – meets the requirements of UL 181B-C, for securing UL Listed non-metallic air ducts and air connectors.

UL LISTED US Pan-Ty® Lashing Ties – Nylon 6.6

- For indoor use
- Typically used for heavy duty applications
- Among the strongest Pan-Ty® Cable Tie available

- Can be used with MCEH mounting clip, see page B1.22
- UL Listed for use in plenum or air handling spaces per NEC except PLT.6SM and PLT5H/6H/8H/13H



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N			
Extra-Heavy Cross Section – Plenum Rated													
PLT2EH-C	9.0	229	0.500	12.7	0.075	1.9	2.00	51	250	1112	GS4EH-E, ST3EH	100	1000
PLT5EH-Q	20.1	511	0.500	12.7	0.075	1.9	5.00	127	250	1112		25	250
PLT6EH-Q	22.2	564	0.500	12.7	0.075	1.9	6.00	152	250	1112		100	1000
PLT8EH-C	28.3	719	0.500	12.7	0.085	2.2	8.00	203	250	1112		100	500
PLT10EH-C	34.2	869	0.500	12.7	0.085	2.2	10.00	254	250	1112			
PLT12EH-C	40.1	1019	0.500	12.7	0.085	2.2	12.00	305	250	1112			