

FASTER. SAFER. EASIER.



Save time and money
with every punch.



Save time and money with every punch!

From the leaders in knockout technology comes the new SPEED PUNCH™ System. The patent pending “no-thread” design eliminates cross-threading, while the innovative SPEED LOCK mechanism quickly secures the punch in place. This means longer tool life and faster punches, saving you time and money on the job. SPEED PUNCH™ is available in ISO 16 to ISO 63 and PG 16 metric sizes and two kit configurations.

UP TO
3X
FASTER



SPEED LOCK mechanism quickly secures the entire system in place:
Punch more holes in less time.



“No-thread” punch design quickly and easily slides on/off draw stud:
The fastest punch system on the market today.

Rugged, durable grooves hold up on the job:
No more thread damage and costly down time.



Matched die heights eliminate need for additional spacers:
Fewer extra parts to lose on the job site.

Standard draw stud end:
Works with your existing hydraulic and battery-operated punch drivers.



LS50-L FLEX

In combination with the hydraulic punching tool LS50-L Flex it represents the state of the art in performance and speed.





1

Slide

Slide die and punch onto draw stud:

"No-thread" design eliminates cross-threading.



2

Secure

Secure SPEED LOCK onto draw stud:

Faster setup and disassembly.



3

Punch

Punch hole:

Save time and money with every punch!

Highlights

- Simple operation and great time-saving due to speed lock system
- Suitable for mild steel (St37), plastic and aluminum up to 3,5 mm thick
- Use with the LS50-L FLEX battery-operation driver for the ultimate in speed and performance



**SAVE TIME
AND MONEY
WITH EVERY
PUNCH.**

Ordering Information



Scan to watch the video
www.youtube.com/greenleedemo

- 1** **SPEED PUNCH™ set**
ISO 16 - 40
Part No.
52055439SET



- 2** **SPEED PUNCH™ set**
ISO 16 - 63
Part No.
52055440SET



Part No.	Description	Qty
1 52055439SET	SPEED PUNCH™ set ISO 16 - 40	1
2 52055440SET	SPEED PUNCH™ set ISO 16 - 63	1
52055431	Punch & Die ISO 16 (16,2 mm)	1
52055432	Punch & Die ISO 20 (20,4 mm)	1
52055433	Punch & Die PG 16 (22,5 mm)	1
52055434	Punch & Die ISO 25 (25,4 mm)	1
52055435	Punch & Die ISO 32 (32,5 mm)	1
52055436	Punch & Die ISO 40 (40,5 mm)	1
52055437	Punch & Die ISO 50 (50,8 mm)	1
52055438	Punch & Die ISO 63 (64,0 mm)	1
52055439	SPEED LOCK & Draw stud 9,5 mm for ISO 16/20/25 and PG 16	1
52055440	SPEED LOCK & Draw stud 19 mm for ISO 32/40/50/63	1

Strong brands for your success:

Klauke®

 **GREENLEE**
A Textron Company

Gustav Klauke GmbH

Auf dem Knapp 46
D-42855 Remscheid

Phone: +49 (0) 2191 / 907 - 0
Fax: +49 (0) 2191 / 907 - 205

E-Mail: info@klauke.textron.com
Internet: www.klauke.com