### HYDRAULIC CUTTING TOOL

# HT-TC065

industrial application

### MAIN APPLICATIONS

### specifically designed to cut Copper, Aluminium and Telecommunications cable having Ø max 65 mm

STORAGE		TECHNICAL FEATURES	
Туре	CVB-010	Max cutting Ø mm	65
Dimensions mm L x W	545 x 160	Dimensions mm	
Weight kg	0,15	Length	523
Supplied with the tool	√	Width	129
		Weight kg	5



### HYDRAULIC CUTTING HEAD

ndustrial application

#### MAIN APPLICATIONS

specifically designed to cut Copper, Aluminium and Telecommunications cable having Ø max 65 mm

#### STORAGE

Туре	VAL-TC065-SC*			
Dimensions mm L x W x H	459 x 231 x 122			
Weight kg	3,6			
Supplied with the tool	√			
*C. Hall I. Construct of the board				

\*Suitable for storage of the head





Hand operated hydraulic tool specifically designed to cut Copper, Aluminium and Telecommunications cable having a max overall diameter of 65 mm. The tool features a double speed action.

The blades are manufactured from high strength special Steel, heat treated to ensure a long service life. The head can be easily opened to allow the cutting of running cables.

The head can rotate through 320 degrees, to enable the operator to work in the most comfortable position.

HT-TC065 features an automatic safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.

## **TC065-SC**



Hydraulic cutting head complete with quick automatic coupler for connection to a hydraulic pump with a working pressure of 700 bar max, (see page 212-218) TC065-SC features the same cutting capability as HT-TC065.

The open head and the "scissor" movement of the blades facilitate the cutting of running cables.

() CEMBRE