


VP RP BP GP

HALOGEN FREE INSULATED TERMINALS

P range funnel entry - for Copper conductors



The "P" range of terminals has been designed, to meet the increasing demands for improved safety and reliability of electrical connectors.

The Polycarbonate insulation, is a Halogen free, self extinguishing thermoplastic material class V0 (UL 94). The unique funnel shaped entry of the insulation sleeve, guarantees to-


tal insertion of the conductor strands into the terminal barrel, creating a secure and reliable, electrical and mechanical connection.

The operating temperature range is - 20 to + 115°C (Surge + 130°C). Recommended crimping tools are shown on pages 108 to 129, 168.




Certified according to
EN 45545-2:2013

pin terminals




Conductor Size sqmm (AWG)	Type	Dimensions mm				Quantity Box/Bag
		Ø	B	P	L	
 0,2÷0,5 (24÷20)	VP-P10	3,0	1,0	9,8	20,2	4.000/100
	RP-P8	4,0	1,6	7,8	17,9	3.000/100
 0,25÷1,5 (22÷16)	RP-P10	4,0	1,6	9,8	19,9	3.000/100
	RP-P12	4,0	1,6	12,0	22,1	3.000/100
 1,5÷2,5 (16÷14)	BP-P8	4,9	1,7	7,8	17,9	3.000/100
	BP-P10	4,9	1,8	9,8	19,9	3.000/100
	BP-P12	4,9	1,8	11,8	21,9	2.500/100
 4÷6 (12÷10)	GP-P10	6,6	2,2	10,4	24,5	1.000/100
	GP-P12	6,6	2,2	12,6	26,7	1.000/100
	GP-P14	6,6	2,2	14,6	28,7	1.000/100

blade terminals



Conductor Size sqmm (AWG)	Type	Dimensions mm				Quantity Box/Bag
		Ø	B	P	L	
 0,2÷0,5 (24÷20)	VP-PP12/19	3,0	1,9	12,4	22,4	4.000/100
	RP-PP12	4,0	3,0	12,8	22,9	3.000/100
 0,25÷1,5 (22÷16)	RP-PP12/1	4,0	3,0	11,3	21,4	3.000/100
	RP-PP12/19	4,0	1,9	13,2	23,3	3.000/100
	RP-PP12/23	4,0	2,3	13,2	23,3	2.500/100
	RP-PP14	4,0	3,0	14,8	24,9	2.500/100
	RP-PP16/23	4,0	2,3	17,2	27,3	2.500/100
	BP-PP12	4,9	3,5	12,8	22,9	2.500/100
 1,5÷2,5 (16÷14)	BP-PP12/25	4,9	2,5	13,3	23,4	2.000/100
	BP-PP12/29	4,9	2,9	13,3	23,4	2.500/100
	BP-PP16/25	4,9	2,5	17,2	27,3	2.500/100
	GP-PP12	6,6	4,0	13,3	27,4	1.000/100
 4÷6 (12÷10)	GP-PP17	6,6	2,9	19,1	33,2	1.000/100


hooked blade terminals



Conductor Size sqmm (AWG)	Type	Dimensions mm					Quantity Box/Bag
		Ø	B	P	L	X	
 0,25÷1,5 (22÷16)	RP-PPL30*	4,0	3,0	17,5	28,3	1,7	3.000/100
	RP-PPL46*	4,0	4,6	17,5	28,3	1,7	3.000/100
 1,5÷2,5 (16÷14)	BP-PPL30*	4,9	3,0	17,5	28,3	1,7	2.500/100
	BP-PPL46*	4,9	4,6	17,5	28,8	1,7	2.500/100
 4÷6 (12÷10)	GP-PPL46*	6,6	4,6	17,5	32,6	1,9	1.000/100


*Not UL approved

ring terminals



Cond. Size sqmm (AWG)	Ø Stud mm	Type	Dimensions mm						Quantity Box/Bag
			Ø	B	M	N	L	d	
 0,2÷0,5 (24÷20)	2	VP-M2*	3,0	5,6	4,5	2,8	17,5	2,2	4.000/100
	3	VP-M3	3,0	5,6	4,5	2,8	17,5	3,2	4.000/100
	3,5	VP-M3.5	3,0	5,6	4,5	2,8	17,5	3,7	4.000/100
	4	VP-M4	3,0	7,0	6,5	3,5	20,2	4,3	4.000/100
	5	VP-M5	3,0	7,8	7,1	3,9	21,2	5,3	4.000/100
	6	VP-M6*	3,0	9,4	8,1	4,7	23,0	6,4	4.000/100
 0,25÷1,5 (22÷16)	2	RP-M2*	4,0	5,6	4,5	2,8	17,4	2,2	3.000/100
	3	RP-M3	4,0	5,6	4,5	2,8	17,4	3,2	3.000/100
	3,5	RP-M3.5	4,0	5,6	4,5	2,8	17,4	3,7	3.000/100
	3,5	RP-M3.5/1	4,0	6,2	7,1	3,1	20,2	3,7	3.000/100
	4	RP-M4	4,0	7,0	6,5	3,5	20,1	4,3	3.000/100
	4	RP-M4/3	4,0	7,8	7,1	3,9	21,1	4,3	3.000/100
	5	RP-M5	4,0	7,8	7,1	3,9	21,1	5,3	3.000/100
	6	RP-M6	4,0	9,4	8,1	4,7	22,9	6,4	2.500/100
	6	RP-M6/1	4,0	12,0	10,3	6,0	26,4	6,4	2.000/100
	7	RP-M7	4,0	9,4	8,1	4,7	22,9	7,2	2.500/100
	8	RP-M8	4,0	12,0	10,3	6,0	26,4	8,4	2.500/100
	10	RP-M10	4,0	15,5	13,0	7,7	30,9	10,5	2.000/100
 1,5÷2,5 (16÷14)	12	RP-M12	4,0	18,0	15,5	9,0	34,6	13,0	2.000/100
	2	BP-M2*	4,9	5,6	5,0	2,8	17,9	2,2	2.500/100
	3	BP-M3	4,9	5,6	5,0	2,8	17,9	3,2	2.500/100
	3,5	BP-M3.5	4,9	5,6	5,0	2,8	17,9	3,7	2.500/100
	3,5	BP-M3.5/1	4,9	6,2	6,5	3,1	19,7	3,7	2.500/100
	4	BP-M4	4,9	8,0	6,5	4,0	20,6	4,3	2.500/100
	5	BP-M5	4,9	8,0	7,5	4,0	21,6	5,3	2.500/100
	6	BP-M6	4,9	9,4	8,6	4,7	23,4	6,4	2.000/100
	6	BP-M6/1	4,9	12,0	10,3	6,0	26,4	6,4	2.500/100
	6	BP-M6/2*	4,9	8,4	5,4	4,2	19,7	6,4	2.500/100
	7	BP-M7	4,9	10,0	7,8	5,0	22,9	7,2	2.500/100
	8	BP-M8	4,9	12,0	10,3	6,0	26,4	8,4	1.500/100
 4÷6 (12÷10)	10	BP-M10	4,9	15,5	13,0	7,7	30,9	10,5	1.500/100
	12	BP-M12	4,9	18,0	15,5	9,0	34,6	13,0	1.500/100
	3	GP-M3	6,6	8,0	8,1	4,0	26,2	3,2	1.000/100
	3,5	GP-M3.5	6,6	8,0	8,1	4,0	26,2	3,7	1.500/100
	4	GP-M4	6,6	9,0	8,1	4,5	26,7	4,3	1.000/100
	5	GP-M5	6,6	9,0	8,1	4,5	26,7	5,3	1.000/100
	6	GP-M6	6,6	11,0	11,1	5,5	30,7	6,4	1.000/100
	6	GP-M6/1	6,6	11,0	8,1	5,5	27,7	6,4	1.000/100
	7	GP-M7	6,6	11,0	11,1	5,5	30,7	7,2	1.000/100
	8	GP-M8	6,6	13,6	12,1	6,8	33,0	8,4	1.000/100
	8	GP-M8/1*	6,6	11,0	8,1	5,5	27,7	8,4	1.000/100
	10	GP-M10	6,6	13,6	12,1	6,8	33,0	10,5	1.000/100
	10	GP-M10/1	6,6	15,5	13,8	7,7	35,7	10,5	1.000/100
	12	GP-M12	6,6	19,0	15,1	9,5	38,7	13,0	500/100
	14	GP-M14	6,6	21,0	16,1	10,5	40,7	15,0	500/100
	16	GP-M16	6,6	24,0	17,1	12,0	43,2	17,0	500/100

fork/spade terminals



Cond. Size sqmm (AWG)	Ø Stud mm	Type	Dimensions mm						Quantity Box/Bag
			Ø	B	M	N	L	d	
 0,2÷0,5 (24÷20)	3	VP-U3	3,0	5,5	5,5	4,0	18,7	3,2	4.000/100
	3,5	VP-U3.5	3,0	6,0	6,5	3,8	19,5	3,7	4.000/100
	4	VP-U4	3,0	6,5	7,5	3,7	20,4	4,3	4.000/100
	4	VP-U4	3,0	6,5	7,5	3,7	20,4	4,3	4.000/100
 0,25÷1,5 (22÷16)	3	RP-U3	4,0	5,5	5,5	4,0	19,6	3,2	3.000/100
	3,5	RP-U3.5	4,0	6,0	6,5	3,8	20,4	3,7	3.000/100
	3,5	RP-U3.5/2	4,0	6,4	6,5	3,8	20,4	3,7	3.000/100
	4	RP-U4	4,0	6,5	7,5	3,7	21,3	4,3	3.000/100
	4	RP-U4/1	4,0	8,5	7,5	3,7	21,3	4,3	3.000/100
	4	RP-U4/2	4,0	7,5	7,5	3,7	21,3	4,3	3.500/100
	5	RP-U5	4,0	8,5	7,5	3,7	21,3	5,3	3.000/100
	5	RP-U5/1*	4,0	9,4	7,5	3,7	21,3	5,3	3.000/100
	6	RP-U6	4,0	9,4	8,1	4,7	22,9	6,4	2.000/100
	6	RP-U6/1	4,0	12,0	9,2	7,1	26,4	6,4	2.000/100
	8	RP-U8	4,0	14,0	10,0	6,3	26,4	8,4	2.000/100
	10	RP-U10	4,0	17,5	13,0	7,7	30,9	10,5	1.500/100
 1,5÷2,5 (16÷14)	12	RP-U12	4,0	20,0	15,5	9,0	34,6	13,0	1.500/100
	3	BP-U3	4,9	5,5	5,5	4,0	19,6	3,2	2.500/100
	3,5	BP-U3.5	4,9	6,4	6,5	3,8	20,4	3,7	2.500/100
	3,5	BP-U3.5/1*	4,9	7,2	6,5	3,8	20,4	3,7	2.500/100
	4	BP-U4	4,9	6,5	7,5	3,7	21,3	4,3	2.500/100
	4	BP-U4/1	4,9	8,5	7,5	3,7	21,3	4,3	3.000/100
	4	BP-U4/2	4,9	7,5	7,5	3,7	21,3	4,3	2.000/100
	5	BP-U5	4,9	8,5	7,5	3,7	21,3	5,3	2.000/100
	6	BP-U6	4,9	9,4	8,1	4,7	22,9	6,4	2.000/100
	6	BP-U6/1	4,9	12,0	9,2	7,1	26,4	6,4	2.000/100
	8	BP-U8	4,9	14,0	10,0	6,3	26,4	8,4	1.500/100
	10	BP-U10	4,9	17,5	13,0	7,7	30,9	10,5	2.000/100
 4÷6 (12÷10)	12	BP-U12	4,9	20	15,5	9,0	34,6	13,0	1.500/100
	3,5	GP-U3.5	6,6	7,5	8,5	3,9	26,5	3,7	1.000/100
	4	GP-U4	6,6	7,5	8,0	4,4	26,5	4,3	1.000/100
	5	GP-U5	6,6	9,5	8,0	4,4	26,5	5,3	1.000/100
	6	GP-U6	6,6	10,0	11,0	5,5	30,6	6,4	1.000/100
	8	GP-U8	6,6	13,5	12,0	8,0	34,1	8,4	1.000/100
	10	GP-U10	6,6	15,5	13,0	8,0	35,1	10,5	1.000/100
	10	GP-U10/1	6,6	17,5	13,8	7,7	35,7	10,5	1.000/100
	12	GP-U12	6,6	21,0	15,1	9,5	38,7	13,0	500/100
	14	GP-U14	6,6	23,0	16,1	10,5	40,7	15,0	500/100
	16	GP-U16	6,6	26,0	17,1	11,5	42,7	17,0	500/100

*Made to order

RF-F BF-F GF-F



Recommended crimping tools are shown on pages 108 to 129, 168.

Polycarbonate insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-F305	2,8 x 0,5	3.000/100
	RF-F308*	2,8 x 0,8	3.000/100
	RF-F405	4,8 x 0,5	2.500/100
	RF-F408	4,8 x 0,8	2.500/100
1,5÷2,5 (16÷14)	RF-F608	6,35 x 0,8	2.500/100
	BF-F405	4,8 x 0,5	2.500/100
	BF-F408	4,8 x 0,8	2.500/100
	BF-F608	6,35 x 0,8	1.500/100
4÷6 (12÷10)	GF-F608	6,35 x 0,8	1.000/100

Certified according to
EN 45545-2:2013


HF
HALOGEN
FREE

cULUS
File no. E212000

Polycarbonate fully insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-F305P	2,8 x 0,5	2.000/100
	RF-F308P*	2,8 x 0,8	2.000/100
	RF-F405P	4,8 x 0,5	1.500/100
	RF-F408P	4,8 x 0,8	1.500/100
1,5÷2,5 (16÷14)	RF-F608P	6,35 x 0,8	1.000/100
	BF-F405P	4,8 x 0,5	1.500/100
	BF-F408P	4,8 x 0,8	1.500/100
	BF-F608P	6,35 x 0,8	1.000/100
4÷6 (12÷10)	GF-F608P	6,35 x 0,8	800/100

RF-M BF-M GF-M



Recommended crimping tools are shown on pages 108 to 129, 168.

Polycarbonate insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-M608	6,35 x 0,8	3.000/100
1,5÷2,5 (16÷14)	BF-M608	6,35 x 0,8	2.000/100
4÷6 (12÷10)	GF-M608	6,35 x 0,8	1.000/100

Certified according to
EN 45545-2:2013


HF
HALOGEN
FREE

cULUS
File no. E212000

Polycarbonate fully insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-M608P	6,35 x 0,8	1.000/100
1,5÷2,5 (16÷14)	BF-M608P	6,35 x 0,8	1.000/100

RF-FM BF-FM RF-B BF-B



Recommended crimping tools are shown on pages 108 to 129, 168.

Polycarbonate insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Tab Size mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-FM608	6,35 x 0,8	1.000/100
1,5÷2,5 (16÷14)	BF-FM608	6,35 x 0,8	1.000/100

BULLET AND SOCKET

for Copper conductors

Certified according to
EN 45545-2:2013

HF
HALOGEN
FREE

cULUS
File no. E212000

Polycarbonate insulated terminals partially reinforced with Copper sleeve

Conductor Size sqmm (AWG)	Type	Ø mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	RF-BM4*	4	2.500/100
	RF-BF4*	4	800/100
1,5÷2,5 (16÷14)	BF-BM5*	5	2.000/100
	BF-BF5*	5	800/100

*Not UL approved