
EBT premium uncoated SS304 ball-lock ties

The EBT premium uncoated range have a non-releasable locking mechanism offering infinite adjustment along the length of the cable tie. Suitable for use in the most arduous conditions or where additional security, strength, fire and chemical resistance is required. Manufactured in the UK, these cable ties are used in all industries from mass transit, shipbuilding, oil rigs, mining and chemical industries. The unique "end of tail" design ensures a smooth and guided entry to the cable tie head at installation.

Part Number	Material	Pack Qty	Length	Width	Max Bundle	Min Tensile
		(pcs)	(mm)	(mm)	Dia (mm)	Strength (N)
EBT5SS	SS 304	100	127	4.6	25	900
EBT8SS	SS 304	100	201	4.6	50	900
EBT14SS	SS 304	100	362	4.6	102	900
EBT20SS	SS 304	100	521	4.6	152	900
EBT27SS	SS 304	100	681	4.6	203	900
EBT33SS	SS 304	100	838	4.6	254	900
EBT8HS	SS 304	50	201	7.9	50	2000
EBT14HS	SS 304	50	362	7.9	102	2000
EBT20HS	SS 304	50	521	7.9	152	2000
EBT27HS	SS 304	50	681	7.9	203	2000
EBT33HS	SS 304	50	838	7.9	254	2000





- 2 strap widths available
- High tensile strength
- Fast, secure installation
- Weather, UV and corrosion resistant
- Flame retardant
- Excellent chemical resistance
- 304 Grade Stainless Steel
- Smooth edges RoHS and REACH compliant

Operating Temperatures

-80°C to +538°C Cable tie:

Tensioning Tools

THT

- For 4.6 & 7.9mm widths
- Ergonomic T-Handle design
- Integrated ratchet system
- Simple tensioning mechanism
- Tail coils to a safe' neat finish

ECTT2



- For 4 6 & 7 9mm widths
- Side entry for positioning of tie
- Adjustable tensioning
- Single handed operation
- Automatic cut off of excess tail

EFSST



- For 4.6 & 7.9mm widths
- Ergonomic T-Handle design
- Integrated ratchet system
- Simple tensioning mechanism
- Tail coils to a safe' neat finish

MK9SST



- For ties up to 16mm wide
- Side entry for tie
- Fully adjustable tensioning
- Single handed operation
- Automatic cut off, with no sharp edges
- Non slip ergonomic handle









