


HT-FL74

PULLER-TYPE HOLE PUNCHING TOOLS

general features



MAIN APPLICATIONS

specifically designed for hole punching stainless Steel, mild Steel, fibreglass and plastic sheet materials up to 3,5 mm thickness

Hand operated hydraulic tool specifically designed for hole punching stainless Steel, mild Steel, fibreglass and plastic sheet materials up to 3,5 mm thickness. Compact, lightweight and easy to handle. The tool is supplied complete with plastic case VAL P28 for protection and storage when not in use. Supplied with Pullers TD-11, TD-19 and spiral bit Ø 11,5 mm. For the punch-die selection chart see page 177.



TECHNICAL FEATURES

Max Punching Ø mm	140
Dimensions mm	
Length	381
Width	138
Weight kg	3,3

STORAGE

Type	VAL-P28
Dimensions mm L x W x H	620 x 360 x 138
Weight kg	2,4
Supplied with the tool	✓
Purchase separately	-



HT-FL75



Hand operated hydraulic tool specifically designed for hole punching stainless Steel, mild Steel, fibreglass and plastic sheet materials up to 3,5 mm thickness. Compact, lightweight and easy to handle. The balanced punching head pivots 180deg through a full 360deg rotation for ease of use in confined spaces.



The tool is supplied complete with plastic case VAL P28 for protection and storage when not in use. Supplied with Pullers TD-11, TD-19 and spiral bit Ø 11,5 mm. For the punch-die selection chart see page 177.

TECHNICAL FEATURES

Max Punching Ø mm	140
Dimensions mm	
Length	452
Width	138
Weight kg	3,67

STORAGE

Type	VAL-P28
Dimensions mm L x W x H	620 x 360 x 138
Weight kg	2,4
Supplied with the tool	✓
Purchase separately	-



KIT-HT-FL75-1



HOLE PUNCHING KIT

general features

KIT-HT-FL75-1

Kit includes:

- HT-FL75 Puller-type hole punching hydraulic tool
- VAL P28 plastic carrying case with accessories
- Puller TD-11
- Puller TD-19
- spiral bit Ø 11,5 mm

4 KIT for round punch:

KIT-RD18.8SS	Pg11
KIT-RD20.5SS	Pg13.5
KIT-RD22.6SS	Pg16
KIT-RD28.5SS	Pg21