

## K-TYPE Pre-printed cable markers

K-Type markers are designed to offer flexibility when it comes to wire and cable identification. Used to identify wire bundles, cable, pipes and conduit, the oval shaped profile has been designed to allow markers to be easily slipped onto a carrier strip and attached using cable ties. K65 markers are ideal for post termination applications or where retrofitting is required.

One standard size of marker, with PVC carrier strips that can hold up to 18 characters. Standard colours are yellow or white with black legends. Colour coded option available.

### Features and benefits

- K-Type markers are a cost effective solution for many commercial wire identification applications
- Self-extinguishing
- Resistant to key industrial fluids, including those used in mass transit, aviation and military
- Versatile marking system for cables, cable bundles and conduit
- Elliptical marker profile allows easy fitting to carrier strips



## K-Type Markers

### Ordering information



Part Number (WHITE)	Part Number (YELLOW)	Part Number (COLOURS)	Pack Size	Dimensions	Cable Range
<b>13619.(legend)</b>	<b>13614.(legend)</b>	<b>13614(colour).(legend)</b>	500pcs	10x6mm	4 to 10mm <sup>2</sup>

(\* directly on to BS6231 Tri-Rated)

## K-Type Carrier Strips

### Ordering information

Part Number	Number of characters	Pack Size	Dimensions (HxW)	Fixing Holes (HxW)
<b>1132000</b>	For up to 7 characters	500pcs	9mm x 66mm	2mm x 8mm
<b>1131000</b>	For up to 12 characters	500pcs	9mm x 97mm	2mm x 8mm
<b>1130000</b>	For up to 18 characters	250pcs	9mm x 134mm	2mm x 8mm



Marker Printed Character	Part Number Black/Yellow	Part Number Black/White	Part Number Colour Coded	Description Quantity of marker reels per pack
A - Z 0 - 9	13614.KIT1	13619.KIT1		36 reels - 1 reel of each A to Z & 0 to 9
0 - 9	13614.KIT2	13619.KIT2		10 reels - 1 reel of each 0 to 9
A - Z	13614.KIT3	13619.KIT3	1361C.C.KIT	26 reels - 1 reel of each A to Z
A - Z 0 - 9 + - / ⊥	13614.KIT4	13619.KIT4		40 reels - 1 reel of each A to Z 0 to 9 + - / ⊥
A - Z 0 - 9 + - / BL	13614.KIT5	13619.KIT5		100pcs of A to Z 0 to 9 + - / blank c/w carry case
A - Z 0 - 9 + - / ⊥	13614.KIT6	13619.KIT6		100pcs of A to Z 0 to 9 + - / ⊥ c/w carry case

0	13614.0	13619.0	13610.0	1 reel marked with 0
1	13614.1	13619.1	13611.1	1 reel marked with 1
2	13614.2	13619.2	13612.2	1 reel marked with 2
3	13614.3	13619.3	13613.3	1 reel marked with 3
4	13614.4	13619.4	13614.4	1 reel marked with 4
5	13614.5	13619.5	13615.5	1 reel marked with 5
6	13614.6	13619.6	13616.6	1 reel marked with 6
7	13614.7	13619.7	13617.7	1 reel marked with 7
8	13614.8	13619.8	13618.8	1 reel marked with 8
9	13614.9	13619.9	13619.9	1 reel marked with 9

A	13614.A	13619.A
B	13614.B	13619.B
C	13614.C	13619.C
D	13614.D	13619.D
E	13614.E	13619.E
F	13614.F	13619.F
G	13614.G	13619.G
H	13614.H	13619.H
I	13614.I	13619.I
J	13614.J	13619.J
K	13614.K	13619.K
L	13614.L	13619.L
M	13614.M	13619.M
N	13614.N	13619.N
O	13614.O	13619.O
P	13614.P	13619.P
Q	13614.Q	13619.Q
R	13614.R	13619.R
S	13614.S	13619.S
T	13614.T	13619.T
U	13614.U	13619.U
V	13614.V	13619.V
W	13614.W	13619.W
X	13614.X	13619.X
Y	13614.Y	13619.Y
Z	13614.Z	13619.Z

1 reel marked with A
1 reel marked with B
1 reel marked with C
1 reel marked with D
1 reel marked with E
1 reel marked with F
1 reel marked with G
1 reel marked with H
1 reel marked with I
1 reel marked with J
1 reel marked with K
1 reel marked with L
1 reel marked with M
1 reel marked with N
1 reel marked with O
1 reel marked with P
1 reel marked with Q
1 reel marked with R
1 reel marked with S
1 reel marked with T
1 reel marked with U
1 reel marked with V
1 reel marked with W
1 reel marked with X
1 reel marked with Y
1 reel marked with Z

+	13614.+	13619.+
-	13614.-	13619.-
/	13614./	13619./
.	13614.DOT	13619.DOT
⊥	13614.EA	13619.EA
~	13614.PH	13619.PH
	13614.BL	13619.BL

1 reel marked with PLUS SIGN
1 reel marked with MINUS / DASH SIGN
1 reel marked with FORWARD SLASH
1 reel marked with DOT
1 reel marked with EARTH SYMBOL
1 reel marked with PHASE SYMBOL
1 reel marked with BLANK (no mark)



## Standard Colours

Black Legend on Yellow Body

Black Legend on White Body

International Colour Coded Numbers

## Material

PVC

## Operating temperature

-45°C up to +70°C.

## Specifications

BS 6746C: 1993

IEC 60304