

with interchangeable dies



### TECHNICAL FEATURES

#### Dimensions mm

Length	240
Width	79
Height	32,5
Weight g	590

A robust and reliable tool designed to optimise the installers time and effort. A single tool body with a range of interchangeable dies allows a quick and simple transfer from one cable/connector combination to another, across a range of applications.

**N.B. :** the tool is supplied without dies, for their choice consult the table on the side.

### KIT AVAILABLE ON REQUEST

#### NEW

##### VALSTAR-N5

- comprising:
- **HWE1N** Manual mechanical tool
  - **KE16-WE** die
  - **RBV-WE**
  - all contained in a sturdy plastic case with extra compartments for interchangeable dies

#### NEW

##### VALSTAR-N6

- comprising:
- **HWE1N** Manual mechanical tool
  - **HB11** wire stripper
  - **MC4-WE** die
  - all contained in a sturdy plastic case with extra compartments for interchangeable dies



### INTERCHANGEABLE DIES TO ORDER SEPARATELY



#### INSULATED CONNECTORS RED, BLUE AND YELLOW

**RBV-WE**

Size 0,5 to 6 mm<sup>2</sup>



#### INSULATED AND UNINSULATED END SLEEVES

**KE6-WE**

Size 0,5 to 6 mm<sup>2</sup>

**KE16-WE**

Size 0,5 to 16 mm<sup>2</sup>

**KE35-WE**

Size 16 to 35 mm<sup>2</sup>



#### CONNECTORS WITH HEAT SHRINKABLE INSULATION

**WLM-WE**

Size 0,5 to 6 mm<sup>2</sup>



#### UNINSULATED CABLE LUGS

**N10-WE**

Size 0,5 to 10 mm<sup>2</sup>



#### OPEN BARREL BRASS CONNECTORS

**F050-WE**

Size 0,08 and 0,5 mm<sup>2</sup>

**F075-WE**

Size 0,05 and 0,75 mm<sup>2</sup>

**F2.5-WE**

Size 0,5 and 2,5 mm<sup>2</sup>




#### PHOTOVOLTAIC CONNECTORS (MULTI-CONTACT)

**MC3-WE**

Size 4 to 6 mm<sup>2</sup>

**MC4-WE**

Size 4 to 6 mm<sup>2</sup>



#### FIBER OPTIC CONNECTOR

**ST-WE**

SMA, SMB, SFR, ST, SC

**SMA-WE**

SMA



#### COAXIAL CONNECTORS

**RG71-WE**

RG58, RG59, RG62

**RG174-WE**

RG58, RG174

**RG179-WE**

RG174, RG179



#### SHIELDED WE CONNECTOR

**RJ45-WE**

RJ45