

PMF-ET

Transparent flat tag holders tie-on

for serie flat cable tags 4 mm

Tie on (tie width max 6 mm) for longitudinal mounting on cables, hoses, tubes and conduit.



Material: plasticised PVC, self extinguishing to class V0 according to UL94, free of Cadmium, Lead, Silicon and Teflon. Resistant to Alkali, Alcohol, Acid and many Solvents.

Operating temperature range: -40°C to +80°C



| | Length mm | Type | For tags mm | Tie: N° x width mm | Quantity |
|--|-----------|---------------|-------------|--------------------|----------|
| | 15 | 63020 | 4 x 15 | 1 x 6 mm | 2.000 |
| | 20 | 63040N | 4 x 20 | 1 x 6 mm | 2.000 |
| | 30 | 63070 | 4 x 30 | 1 x 6 mm | 1.000 |
| | 40 | 63090 | 4 x 40 | 2 x 6 mm | 500 |
| | 20 | 64040 | 9 x 20 | 1 x 6 mm | 1.000 |
| | 35 | 64050 | 9 x 35 | 2 x 6 mm | 500 |
| | 17 | 65000 | 15 x 17 | 1 x 6 mm | 500 |
| | 27 | 65010 | 15 x 27 | 1 x 6 mm | 500 |
| | 49 | 65020 | 15 x 49 | 2 x 6 mm | 250 |
| | 67 | 65030 | 15 x 67 | 2 x 6 mm | 250 |

It is advisable to select the holder size based on the actual external diameter of the cable rather than its indicative c.s.a, due to variations in insulation thickness and conductor format.

Consult us for holders in other lengths.

Use holders only with designated cable tags of the same length.



flat cable tags, 4 mm MG-TPMF page 12
 flat cable tags, 4 mm TPM-ROLL page 62
 flat cable tags, 9 mm MG-TAP page 26
 flat cable tags, 9 mm TAP-ROLL page 68

flat cable tags, 15 mm MG-TAPW page 28
 flat cable tags, 15 mm TAR-ROLL page 63
 cable ties page 135

