

MG-ETF

Cable & conduit tags tie-on

precut, one piece tags

MG-ETF tags are used with cable ties for marking large diameter cables, hoses, tubes and conduit.

Cable tie max width 4,8 mm.



MG-ETF-PO

NEW

Material: Polyolefin, Silicon free, self extinguishing class HB: according to UL94; material PO10080 is EN 45545-2 approved, for railway applications. Use Ribbon MG-EPTR PREMIUM to print on Polyolefin tags.

Operating temperature range: -55°C to +105°C



Size mm	Type											Print area mm	Tags per sheet	Quantity	SW code
	white	yellow	grey	red	blue	green	orange	dark brown	pink	violet	black				
13 x 60	64591-PO	64541-PO	64581-PO	64521-PO	64561-PO	64551-PO	64531-PO	64571BR-PO	64571-PO	64571VI-PO	64501-PO	11 x 44	16	400	586
15 x 95	64593-PO	64543-PO	64583-PO	64523-PO	64563-PO	64553-PO	64533-PO	64573BR-PO	64573-PO	64573VI-PO	64503-PO	13 x 73	7	175	594
22 x 26	64590-PO	64540-PO	64580-PO	64520-PO	64560-PO	64550-PO	64530-PO	64570BR-PO	64570-PO	64570VI-PO	64500-PO	9 x 24	15	375	587
22 x 29	64592-PO	64542-PO	64582-PO	64522-PO	64562-PO	64552-PO	64532-PO	64572BR-PO	64572-PO	64572VI-PO	645002-PO	16,5 x 20	15	375	588
26 x 60	64597-PO	64547-PO	64587-PO	64527-PO	64567-PO	64557-PO	64537-PO	64577BR-PO	64577-PO	64577VI-PO	64507-PO	24 x 37	15	200	595



13x60


22x26

22x29



Directly on cables using appropriate cable ties.
Use the ribbon PREMIUM 991613 to print Polyolefin items.

template with PET support..... page 12
ribbons..... page 13
cable tie max width 4,8 mm..... page 135



MG-ETF



MG-ETF-SBS

Material: SBS Styrene-Butadiene-Styrene, Halogen free, self extinguishing class HB: according to UL94

Operating temperature range: -30°C to +70°C

Size mm	Type											Print area mm	Tags per sheet	Quantity	SW code
	white	yellow	metallic grey	red	blue	green	orange	dark brown	pink	violet	black				
13 x 60	64193-SBS	64143-SBS	64183-SBS	64123-SBS	64163-SBS	64153-SBS	64133-SBS	64173-SBS	64313-SBS	64113-SBS	64103-SBS	11 x 44	16	800	589
15 x 95	64293N-SBS	64243N-SBS	64283N-SBS	64223N-SBS	64263N-SBS	64253N-SBS	64233N-SBS	64273NBR-SBS	64273N-SBS	64273NVI-SBS	64203N-SBS	13 x 73	25	350	594
26 x 60	64198-SBS	64148-SBS	64188-SBS	64128-SBS	64168-SBS	64158-SBS	64138-SBS	64178BR-SBS	64178-SBS	64178VI-SBS	64108-SBS	24 x 37	15	400	595

MG-ETF-HF

Material: Polycarbonate, Halogen Free, self extinguishing class V0: according to UL94; the colours white PC10050WH and yellow PC10050YE are EN 45545-2 approved, for railway applications.

Operating temperature range: -40°C to +130°C

Size mm	min. Ø cable mm	Type										Print area mm	Tags per sheet	Quantity	SW code
		white PC10050WH	yellow PC10050YE	metallic grey	red	blue	green	orange	light brown	dark brown	black				
13 x 57	6	54192-HF	54142-HF	54182-HF	54122-HF	54162-HF	54152-HF	54132-HF	54172-HF	54172-1-HF	54102-HF	11 x 35	14	700	581
15 x 95	7	54293-HF	54243-HF									13 x 73	5	250	584
28 x 57	10	54197-HF	54147-HF		54127-HF	54167-HF		54137-HF				26 x 35	6	300	590



Directly on cables using appropriate cable ties.
Use the MG-EPTR PREMIUM ribbon to print FLAT Polycarbonate items.

template with PET support..... page 12
ribbons..... page 13
cable tie max width 4,8 mm page 133

