

L-Series Cu Lugs & Splices



Tubular cable lugs copper 6 - 630 mm², L-series, Standard type

- For stranded conductors e.g. VDE 0295 Class 2
- For pre-rounded sector shaped conductors
- Annealed to optimise crimping properties
- Internal chamfered barrel for easy cable insertion
- Pure E-Cu / Electro tin plated
- Material/Surface: copper acc. to EN 13600/tin plated
- Inspection hole

mm ²	M5	M6	M8	M10	M12	M14	M16	M20
6	L65FMS	L66FMS	L68FMS	L610FMS	L612FMS			
10	L105FMS	L106FMS	L108FMS	L1010FMS	L1012FMS			
16	L165FMS	L166FMS	L168FMS	L1610FMS	L1612FMS			
25	L255FMS	L256FMS	L258FMS	L2510FMS	L2512FMS	L2514FMS		
35		L356FMS	L358FMS	L3510FMS	L3512FMS	L3514FMS	L3516FMS	
50		L506FMS	L508FMS	L5010FMS	L5012FMS	L5014FMS	L5016FMS	L5020FMS
70		L706FMS	L708FMS	L7010FMS	L7012FMS	L7014FMS	L7016FMS	L7020FMS
95			L958FMS	L9510FMS	L9512FMS	L9514FMS	L9516FMS	L9520FMS
120			L1208FMS	L12010FMS	L12012FMS	L12014FMS	L12016FMS	L12020FMS
150			L1508FMS	L15010FMS	L15012FMS	L15014FMS	L15016FMS	L15020FMS
185				L18510FMS	L18512FMS	L18514FMS	L18516FMS	L18520FMS
240				L24010FMS	L24012FMS	L24014FMS	L24016FMS	L24020FMS
300					L30012FMS	L30014FMS	L30016FMS	L30020FMS
400					L40012FMS	L40014FMS	L40016FMS	L40020FMS
500							L50016FMS	L50020FMS
630							L63016FMS	L63020FMS



Butt connectors copper 0.75 - 630 mm², L-series, Standard Type

- For stranded conductors e.g. VDE 0295 Class 2
- Annealed material optimizes material and crimping characteristics
- With central cable stop
- Pure E-Cu / Electro tin plated

mm ²		mm ²		mm ²		mm ²	
0.75	LV075	10	LV10	70	LV70	240	LV240
1.5	LV15	16	LV16	95	LV95	300	LV300
2.5	LV25	25	LV25	120	LV120	400	LV400
4	LV4	35	LV35	150	LV150	500	LV500
6	LV6	50	LV50	185	LV185	630	LV630

Tools	Series	6 mm ²	10 mm ²	16 mm ²	25 mm ²	35 mm ²	50 mm ²	70 mm ²	95 mm ²	120 mm ²	150 mm ²	185 mm ²	240 mm ²	300 mm ²	400 mm ²	500 mm ²	630 mm ²
K2		•	•	•													
K05L		•	•	•	•	•	•										
K06L				•	•	•	•	•	•	•	•						
K09L						•	•	•	•	•	•						
EKM60IDCFB			•	•	•	•	•	•	•	•	•	•	•				
EK50ML	50 K50ML	•	•	•	•												
EK354CFB/ML	4 K354CFB	•	•	•	•	•	•	•	•	•	•						
EK505CFB	5 K505CFB	•	•	•	•	•	•	•	•	•	•	•	•				
EK6022CFB	22 K6022CFB	•	•	•	•	•	•	•	•	•	•	•	•	•			
EK12032CFB	13 K12032CFB	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
EK135FTCFB	15 K135FTCFB	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Dies	Series	6 mm ²	10 mm ²	16 mm ²	25 mm ²	35 mm ²	50 mm ²	70 mm ²	95 mm ²	120 mm ²	150 mm ²	185 mm ²	240 mm ²	300 mm ²	400 mm ²	500 mm ²	630 mm ²
	50 K50ML	R502	R502	L501625	L501625												
	4 K4	HL46	HL410	HL416	HL425	HL435	HL450	HL470	HL495	HL4120	HL4150						
	5 K5	HL5635	HL51050	HL51670	HL52595	HL5635	HL51050	HL51670	HL52595	HL5120	HL5150	HL5185	HL5240				
	22 K22	L226	L2210	L2216	L2225	L2235	L2250	L2270	L2295	L22120	L22150	L22185	L22240	L22300			
	13 K13	HL1310	HL1316	HL1325	HL1335	HL1350	HL1370	HL1395	HL13120	HL13150	HL13185	HL13240	HL13300	HL13400			
	15 K15	13 series dies (above) used in the EK135FT tool for sizes 10 - 400mm ² with adapter UA15T (supplied with EK135FT tools) HL15500 HL15630															