

EFC-LT Liquid Tight Steel Flexible Conduit



Ordering information

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
EFC-LT-CS16-050	16mm IP67 Flexible Conduit	Black	18	13	50m
EFC-LT-CS20-050	20mm IP67 Flexible Conduit	Black	21	16	50m
EFC-LT-CS25-050	25mm IP67 Flexible Conduit	Black	26	21	50m
EFC-LT-CS32-010	32mm IP67 Flexible Conduit	Black	33	27	10m
EFC-LT-CS20-CP10	20mm IP67 Contractor Pack	Black	21	16	10m
EFC-LT-CS25-CP10	25mm IP67 Contractor Pack	Black	26	21	10m
EFC-LT-NPB16-FF	16mm IP67 Straight Fitting	Self			10pcs
EFC-LT-NPB20-FF	20mm IP67 Straight Fitting	Self			10pcs
EFC-LT-NPB25-FF	25mm IP67 Straight Fitting	Self			10pcs
EFC-LT-NPB32-FF	32mm IP67 Straight Fitting	Self			2pcs
EFC-LT-NPB16-RF	16mm IP67 90° Fitting	Self			10pcs
EFC-LT-NPB20-RF	20mm IP67 90° Fitting	Self			10pcs
EFC-LT-NPB25-RF	25mm IP67 90° Fitting	Self			10pcs
EFC-LT-NPB32-RF	32mm IP67 90° Fitting	Self			2pcs

*All dimensions in mm



Contractors pack

- 10 metres of conduit
- 10 nylon glands
- 10 locknuts

Technical Data



Material PVC Coated Galvanised Steel

Operating Temperature -20°C to +105°C

Compression Strength 400kg/100mm

IP Rating IP67

- High mechanical strength
- Smooth outer jacket
- Manufactured in the UK
- BS EN 61386 compliant
- IP67 rated fittings
- Contractor pack options

EPC-RS Rubber Lined Stainless Steel P-Clips



Ordering information

Part number	Description	Colour	Max Diameter	Material	Pack Size
EPC16RS4	16mm Diameter P-Clip	Self	16	SS304	25pcs
EPC25RS4	21mm Diameter P-Clip	Self	21	SS304	25pcs
EPC25RS4	25mm Diameter P-Clip	Self	25	SS304	25pcs
EPC35RS4	35mm Diameter P-Clip	Self	35	SS304	25pcs

Technical Data



Material Stainless Steel 304

Operating Temperature -40°C to +60°C

- 6.6mm fixing hole
- Fast and simple to install
- Suitable for indoor and outdoor use