

T1

DUCT SERIES

Material: Rigid PVC, self extinguishing
Colour: Grey RAL 7030, White
Standard Length: 2 metres
Standard Unit Supplied:
 Duct complete with cover




T1-F

DUCT SERIES


Material: Rigid PVC, self extinguishing
Colour: Grey RAL 7030
Standard Length: 2 metres
Standard Unit Supplied:
 Duct complete with cover



This duct is ideal for wiring large-sized cables usually employed in power panels. With thick side and base, it has a strong construction and maximum application stability, very good holding also under heavy wiring and longer durability and reliability. Available in a wide range of heights for space optimization inside the electric panel.



BASE 15-25x30



BASE 25-40-60-75-80-100-120-150



Detail of duct body/cover coupling for maximum wire retention and maximum solidity



Blue colour duct recognized for intrinsic safe

Name	Dimensions (mm)					Section mm ²	Packaging metres
	B	H	E	F	G		
T1 15x18 G	15	18	5	7,5	4	200	72
T1 15x30 G	15	30	5	7,5	6	340	64
T1 25x30 G/W/BL*	25	30	5	7,5	8	610	72
T1 15x40 G*	15	40	5	7,5	10	460	48
T1 25x40 G/W	25	40	8	12	12	820	72
T1 40x40 G/W/BL*	40	40	8	12	12	1360	40
T1 60x40 G/BL*	60	40	8	12	12	1970	24
T1 80x40 G	80	40	8	12	12	2680	24
T1 100x40 G	100	40	8	12	12	3380	16
T1 15x60 G	15	60	5	7,5	10	680	32
T1 25x60 G/W/BL*	25	60	8	12	14	1190	48
T1 40x60 G/W/BL*	40	60	8	12	14	2040	36
T1 60x60 G/W/BL*	60	60	8	12	14	3080	24
T1 80x60 G/W	80	60	8	12	14	4150	24
T1 100x60 G/W*	100	60	8	12	14	5250	16
T1 120x60 G	120	60	8	12	14	6300	16
T1 75x125 G/W*	75	125	8	12	20	8398	12
T1 100x125 G/W*	100	125	8	12	20	11415	8

G = GREY RAL 7030

W = WHITE

BL = BLUE RAL 5015

* = Available upon request

Name	Dimensions (mm)					Section mm ²	Packaging metres
	B	H	E	F	G		
T1-F 25x80 G	25	80	8	12	16	1550	48
T1-F 40x80 G	40	80	8	12	16	2700	32
T1-F 60x80 G/W*/BL*	60	80	8	12	16	4140	24
T1-F 80x80 G/W*/BL*	80	80	8	12	16	5660	24
T1-F 100x80 G	100	80	8	12	16	7150	16
T1-F 120x80 G	120	80	8	12	16	8630	16
T1-F 25x100 G/BL*	25	100	8	12	18	2300	16
T1-F 40x100 G	40	100	8	12	18	3310	16
T1-F 60x100 G	60	100	8	12	18	5140	8
T1-F 80x100 G	80	100	8	12	18	7020	8
T1-F 100x100 G/BL*	100	100	8	12	18	8920	8
T1-F 150x100 G/W*	150	100	8	12	18	13570	8

G = GREY RAL 7030

W = WHITE

BL = BLUE RAL 5015

* = Available upon request

Lines T1-F/T1-EF h 80-100

Finger narrowing for easier vertical wiring before the cover is mounted, for correct wire positioning and circuit separation



T1-F