



**Tubular Cable Lugs L Series, Cu with 4 holes, to suit 4 hole transformer fixing**



- ▶ For stranded conductors e.g. BS EN 60228 Class 2
- ▶ For pre-rounded multi-stranded sector shaped conductors
- ▶ Flared cable entry for easy application
- ▶ Inspection hole to check conductor is fully inserted

**Characteristics**


- Suitable for most transformer fixings
- Simple and safe connection due to flat contact surfaces and internal chamfer
- Item identification on cable lug
- Single piece construction

**Material**

- Copper (EN13600)

**Surface**

- Tin-plated to protect against corrosion



Nominal cross section mm <sup>2</sup>	Size of bolt diameter	Part No.	Dimension mm										Weight/ 100 pcs. ~ kg	Packing unit/pcs
			a	b	d1	d2	d4	c1	c2	l	l2	b1		
185	M8	<b>L185B04825FMS</b>	46	61	19	9	24	15	20	84	25	35	19,88	10
240	M8	<b>L240B04825FMS</b>	48	61	21	9	26	15	20	88	25	35	22,77	10
300	M8	<b>L300B04825FMS</b>	52	61	23	9	29,5	15	20	93	25	35	30,78	5
400	M8	<b>L400B04825FMS</b>	50	61	27	9	34	15	20	94	25	35	41,10	5
500	M8	<b>L500B04825FMS</b>	53	61	31	9	38	15	20	99	25	35	47,66	1
630	M8	<b>L630B04825FMS</b>	57	61	34	9	40	15	20	104	25	35	45,17	1
800	M8	<b>L800B04825FMS</b>	67	61	40	9	52	15	20	118	25	35	123	1