

## Plain Betaduct

- Supplied with lid
- Ideal where no break-outs are required or side wall access is infrequent
- Complete cable protection
- 25 sizes, in either grey or black

### Material

Self extinguishing PVC.

### Standard Colours

RAL 7030 grey, black.

### Service Temperature

-15°C to +60°C.

### Flammability

UL94 V-O rated material.

### Standards

Base slots to DIN 43659.

### Approvals


CSA, UL and Lloyds Register.

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Grey RAL 7030 PVC	ORDER CODE Black PVC
15/15	17/17	48	10480011	0920
19/50	23/54	24	10480018	1010
25/20	29/25	24	10480021	0921
25/37.5	29/41	24	10480022	1011
25/50	29/54	24	10480023	0923
25/75	29/80	16	10480024	0924
25/100	29/105	16	10480025	1013
37.5/37.5	41/41	24	10480032	1014
37.5/50	41/54	16	10480033	1015
37.5/75	41/80	16	10480034	1016
37.5/100	41/105	16	10480035	1017
50/25	54/29	24	10480051	1018
50/37.5	54/41	16	10480052	1019
50/50	54/54	16	10480053	0926
50/75	54/80	16	10480054	0927
50/100	54/105	8	10480055	1022
75/37.5	80/41	16	10480072	1023
75/50	80/54	16	10480073	1024
75/75	80/80	16	10480074	0929
75/100	80/105	8	10480075	1026
100/50	105/54	8	10480103	1028
100/75	105/80	8	10480104	1029
100/100	105/115	8	10480105	1030
100/125	105/130	8	10480106	1031
125/75	130/80	8	10480124	0942

Note: Sizes 15/15 and 100/125 are not DIN 43659 (base slots).

## LFH Betaduct

- Supplied with lid
- Choice of Open slot, Closed slot or Plain
- Limited Fire Hazard
- Zero Halogen
- Low smoke
- Wide range of sizes
- Available in black



### Material

Self extinguishing. Modified PPO, Zero Halogen.

### Standard Colours

Black.

### Service Temperature

-30°C to +120°C.

### Flammability

UL94 V-O rated material. BS476 Part 7 Class 1 (Y).

### Standards

Base slots to DIN 43659.

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Open Slot LFH	ORDER CODE Closed Slot LFH	ORDER CODE Plain LFH
25/35	29/38	24	23461	23451	23471
25/50	29/54	24	23462	23452	23472
25/75	29/80	16	23463	23453	23473
50/50	54/54	16	23464	23454	23474
50/75	54/80	16	23465	23455	23475
75/75	80/80	16	23466	23456	23476

Note: Open and Closed slot have 19mm pitching.