

## TWIN THREAD POZI DOUBLE COUNTERSUNK WOODSCREWS - Zinc Plated

| Code       | Size      | Qty Per Box | Qty Per Outer | Price £ Per 1,000 |
|------------|-----------|-------------|---------------|-------------------|
| 0042T45018 | 1/2 x 4   | 200         | 22800         | <b>9.01</b>       |
| 0042T45020 | 5/8 x 4   | 200         | 22800         | <b>9.68</b>       |
| 0042T45022 | 3/4 x 4   | 200         | 22800         | <b>10.50</b>      |
| 0042T45100 | 1 x 4     | 200         | 18000         | <b>12.01</b>      |
| 0042T47020 | 5/8 x 5   | 200         | 22800         | <b>11.00</b>      |
| 0042T49018 | 1/2 x 6   | 200         | 22800         | <b>10.10</b>      |
| 0042T49020 | 5/8 x 6   | 200         | 22800         | <b>10.83</b>      |
| 0042T49022 | 3/4 x 6   | 200         | 18000         | <b>11.55</b>      |
| 0042T49100 | 1 x 6     | 200         | 10000         | <b>13.72</b>      |
| 0042T49114 | 1.1/4 x 6 | 200         | 10000         | <b>15.87</b>      |
| 0042T49118 | 1.1/2 x 6 | 200         | 5600          | <b>19.48</b>      |
| 0042T49200 | 2 x 6     | 200         | 5600          | <b>25.98</b>      |
| 0042T52022 | 3/4 x 7   | 200         | 18000         | <b>15.00</b>      |
| 0042T52100 | 1 x 7     | 200         | 10000         | <b>15.87</b>      |
| 0042T52114 | 1.1/4 x 7 | 200         | 5600          | <b>18.76</b>      |
| 0042T52118 | 1.1/2 x 7 | 200         | 5600          | <b>21.51</b>      |
| 0042T54018 | 1/2 x 8   | 200         | 18000         | <b>15.00</b>      |
| 0042T54020 | 5/8 x 8   | 200         | 18000         | <b>15.76</b>      |
| 0042T54022 | 3/4 x 8   | 200         | 10000         | <b>15.87</b>      |
| 0042T54100 | 1 x 8     | 200         | 10000         | <b>18.76</b>      |
| 0042T54114 | 1.1/4 x 8 | 200         | 5600          | <b>21.65</b>      |
| 0042T54118 | 1.1/2 x 8 | 200         | 5600          | <b>24.53</b>      |

| Code       | Size       | Qty Per Box | Qty Per Outer | Price £ Per 1,000 |
|------------|------------|-------------|---------------|-------------------|
| 0042T54122 | 1.3/4 x 8  | 200         | 5600          | <b>29.39</b>      |
| 0042T54200 | 2 x 8      | 200         | 4200          | <b>32.47</b>      |
| 0042T54214 | 2.1/4 x 8  | 200         | 4200          | <b>41.84</b>      |
| 0042T54218 | 2.1/2 x 8  | 200         | 4200          | <b>46.18</b>      |
| 0042T54300 | 3 x 8      | 200         | 4200          | <b>53.07</b>      |
| 0042T56100 | 1 x 10     | 200         | 5600          | <b>25.25</b>      |
| 0042T56114 | 1.1/4 x 10 | 200         | 5600          | <b>28.86</b>      |
| 0042T56118 | 1.1/2 x 10 | 200         | 4200          | <b>33.92</b>      |
| 0042T56122 | 1.3/4 x 10 | 200         | 4200          | <b>36.79</b>      |
| 0042T56200 | 2 x 10     | 200         | 4200          | <b>43.29</b>      |
| 0042T56218 | 2.1/2 x 10 | 100         | 2800          | <b>56.66</b>      |
| 0042T56300 | 3 x 10     | 100         | 2800          | <b>68.54</b>      |
| 0042T56318 | 3.1/2 x 10 | 100         | 2100          | <b>88.74</b>      |
| 0042T56400 | 4 x 10     | 100         | 2100          | <b>108.81</b>     |
| 0042T58118 | 1.1/2 x 12 | 200         | 4200          | <b>55.55</b>      |
| 0042T58200 | 2 x 12     | 200         | 4200          | <b>60.60</b>      |
| 0042T58218 | 2.1/2 x 12 | 100         | 2100          | <b>77.59</b>      |
| 0042T58300 | 3 x 12     | 100         | 2100          | <b>90.89</b>      |
| 0042T58318 | 3.1/2 x 12 | 100         | 2100          | <b>108.21</b>     |
| 0042T58400 | 4 x 12     | 100         | 2100          | <b>126.25</b>     |

Fully threaded to 1 1/4"  
30 outers per pallet



Deep Cross Drive Recess.

Double Countersunk for deeper recess and added strength.

Through Hardened for ductility.

40° Twin Thread for speed of insertion and greater pull out resistance.

Zinc plated to 5 microns.

Sharp point for fast start.



The most popular screw in the UK. For general applications into softwood and various types of hardwood.

Hardness:  
Core = Min. 270HV - Max. 420HV,  
Surface = Min. 450HV - Max. 720HV

Made with C1022 Premium Steel.