# **ECTB** self adhesive nylon cable tie base


With a self adhesive cable tie base you can create a cable tie mounting point anywhere. Use of a cable tie base ensures cables are routed and fixed safely and in an organised fashion.


Before application please ensure surfaces are clean and grease free. For uneven surfaces you can use the central fixing hole and screw in to position.



### Ordering information

| BLACK<br>Part Number | NATURAL<br>Part Number | Pack Qty<br>(pcs) | Length<br>(mm) | Width<br>(mm) | Height<br>(mm) | Fixing Hole<br>Dia (mm) | Cable Tie<br>Slot (mm) |
|----------------------|------------------------|-------------------|----------------|---------------|----------------|-------------------------|------------------------|
| ECTB19B              | ECTB19N                | 100               | 19.0           | 19.0          | 4.4            | 3.5                     | 4.0                    |
| ECTB28B              | ECTB28N                | 100               | 27.7           | 27.7          | 5.7            | 5.7                     | 5.3                    |
| ECTB40B              | ECTB40N                | 100               | 38.1           | 38.1          | 5.4            | 6.0                     | 9.3                    |





# **Technical Datasheet**







#### Colour

Black or natural

### **Material**

Halogen free Polyamide 6.6

# **Features**

Halogen free UL94 V2 Self adhesive backing Single fixing hole

### **Operating temperature**

-40°C up to +85°C

# **ESMB** screw mount nylon cable tie base


Designed to hold larger cables or cable bundles, these screw mount bases are used across many industries and offer a very secure cable tie mounting point.


The saddles can easily be fixed in place by means of a screw or bolt using the fixing hole, and can accommodate a range of cable ties widths.



### **Ordering information**

| BLACK<br>Part Number | NATURAL<br>Part Number | Pack Qty<br>(pcs) | Length<br>(mm) | Width<br>(mm) | Height<br>(mm) | Fixing Hole<br>Dia (mm) | Cable Tie<br>Slot (mm) |
|----------------------|------------------------|-------------------|----------------|---------------|----------------|-------------------------|------------------------|
| ESMB1B               | ESMB1N                 | 100               | 14.9           | 9.5           | 7.2            | 3.7                     | 4.8                    |
| ESMB2B               | ESMB2N                 | 100               | 21.9           | 15.9          | 9.7            | 5.0                     | 9.0                    |











#### Colour

Black or natural

#### **Material**

Halogen free Polyamide 6.6

### **Features**

Halogen free UL94 V2 Single fixing hole Suitable for screw or bolt

### **Operating temperature**

-40°C up to +85°C