




Pan-Ty® Cable Ties – Heat Stabilized Nylon 6.6

- For high temperature applications up to 239°F (115°C) – indoor use
- One-piece construction for consistent performance and reliability
- Among the lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N			

Subminiature Cross Section

PLT.6SM-M30	2.8	71	0.070	1.8	0.030	0.8	.60	15	8	36	GTS-E, PTS	1000	50000
-------------	-----	----	-------	-----	-------	-----	-----	----	---	----	------------	------	-------

Miniature Cross Section

PLT.7M-M30	3.1	79	0.090	2.3	0.032	0.8	.68	17	18	80	GTS-E, GS2B-E, PTS, PPTS, STS2	1000	50000
PLT1M-C30	3.9	99	0.098	2.5	0.043	1.1	.87	22	18	80		100	1000
PLT1.5M-M30	5.6	142	0.098	2.5	0.043	1.1	1.25	32	18	80		1000	50000
PLT2M-M30	8.0	203	0.098	2.5	0.043	1.1	2.00	51	18	80		1000	25000

Intermediate Cross Section

PLT1.5I-C30	5.6	142	0.142	3.6	0.045	1.1	1.38	35	40	178	GTS-E, GS2B-E, PTS, PPTS, STS2	100	1000
PLT2I-C30	8.0	203	0.142	3.6	0.045	1.1	2.00	51					
PLT3I-M30	11.4	290	0.145	3.7	0.052	1.3	3.00	76	40	178		1000	10000
PLT4I-M30	14.5	368	0.145	3.7	0.052	1.3	4.00	102					

Standard Cross Section

PLT1S-M30	4.8	122	0.190	4.8	0.052	1.3	1.00	25	50	222	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2	1000	10000
PLT1.5S-M30	6.2	157	0.190	4.8	0.052	1.3	1.50	38					
PLT2S-C30	7.4	188	0.190	4.8	0.052	1.3	1.88	48	50	222		100	1000
PLT2S-M39*	7.4	188	0.190	4.8	0.052	1.3	1.88	48					
PLT2.5S-M30	9.8	249	0.190	4.8	0.052	1.3	2.50	64	50	222		1000	10000
PLT3S-C30	11.5	292	0.190	4.8	0.052	1.3	3.00	76					
PLT4S-C30	14.5	368	0.190	4.8	0.052	1.3	4.00	102					
PLT5S-M30	17.5	445	0.190	4.8	0.052	1.3	5.00	127	50	222		1000	5000

Light-Heavy Cross Section (Straight Tip)

PLT2H-TL30	8.1	206	0.300	7.6	0.075	1.9	2.00	51	120	534	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	250	2500
PLT3H-TL30	11.4	290	0.300	7.6	0.075	1.9	3.00	76					
PLT4H-TL30	14.5	368	0.300	7.6	0.075	1.9	4.00	102					
PLT4H-TL30/147	14.5	368	0.300	7.6	0.060	1.5	4.11	104.5					
PLT7LH-C30	24.7	627	0.300	7.6	0.075	1.9	7.00	178	120	534		100	2000
PLT9LH-C30	30.5	775	0.300	7.6	0.075	1.9	9.00	229	120	534		100	1000

Heavy Cross Section (Straight Tip)

PLT5H-C30	17.7	450	0.350	8.9	0.078	2.0	5.00	127	175	778	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	100	2000
PLT6H-C30	20.9	530	0.350	8.9	0.078	2.0	6.00	152					
PLT8H-C30	30.6	779	0.350	8.9	0.078	2.0	9.00	229					

*Natural heat stabilized material (39).