

MG-VRT-R



Panel plates rivet fixing

Customizable

MG-VRT-R rigid PVC panel plates are used to create name plates, rating plates, data plates using company logos, technical data, serial numbers, EC certification, etc.

Transparent Polycarbonate covers can be used for increased durability.

Consult us for availability of other colors and transparent versions.

Note: UV resistance may vary between colors.

Material: Rigid PVC, self extinguishing class V0 according to UL94; the colors white PVC10050WH and yellow PVC10050YE are UL approved.

Operating temperature range: -22°F to +140°F

Application temperature range: +50°F to +104°F

PVC
SF
-22°F
+140°F
UL US
RoHS COMPLIANT 2011/65/EU

Family	Size mm	Type					Cover	Tags per sheet	Quantity	SW code	
		white PVC10050WH	yellow PVC10050YE	grey	red	green					black
MG-VRT-R	25 x 80	48908	48408					4	200	861	
	25 x 100	48905	48405					4	200	205	
	25 x 140	48946						4	100	824	
	30 x 70	48929						3	150	820	
	32 x 58	48900N	48400N	48700NGY			47590	6	300	200	
	35 x 100	48917	48417	48717GY	48217			3	75	810	
	42 x 78	48901	48401	48701GY			47591	2	100	202	
	50 x 50	48918	48418					4	200	858	
	50 x 100	48997			48297		48197	2	50	844	
	52 x 107	48903	48403	48703GY	48223		47592	2	100	204	
	60 x 100	48941					47596	1	50	821	
	62 x 88	48902	48402	48702GY			47594	1	50	203	
	92 x 118	48913	48413	48713GY	48213	48513	48113	47593	1	50	813
	102 x 138	48928	48428	48728GY	48228		48128	47595	1	50	207
	105 x 110	48904		48704GY					1	50	859



Directly on suitable surfaces.

template with PET support..... page 10
 ribbons page 11
 transparent cover CPT..... page 147



MG-VRT-R

TT FOR SHEET MEDIA

Panel plates rivet fixing, Halogen free

Customizable

MG-VRT-R-HF Polycarbonate panel plates are used to create name plates, rating plates, data plates using company logos, technical data, serial numbers, EC certification, etc.

Transparent Polycarbonate covers can be used for increased durability.

Consult us for availability of other colors and transparent versions.

Note: UV resistance may vary between colors.



Material: Polycarbonate, Halogen Free, self extinguishing class V0 according to UL94; the color white PC10050WH is EN 45545-2 approved.

Operating temperature range: -40°F to +266°F

PC
HF
SF
-40°F
+266°F
EN 45545-2
RoHS COMPLIANT 2011/65/EU

Family	Size mm	Type			Cover	Tags per sheet	Quantity	SW code
		white PC10050WH	matte white	metallic grey				
MG-VRT-R-HF	32 x 58	48900N-HF		48700N-HF	47590	6	300	200
	35 x 100	48917-HF		48717-HF		3	75	810
	42 x 78	48901-HF		48701-HF	47591	2	100	202
	50 x 50	48918-HF		48718-HF		4	200	858
	52 x 107	48903-HF		48703-HF	47592	2	100	204
	62 x 88	48902-HF		48702-HF	47594	1	50	203
	75 x 120	48944-HF				2	50	811
	92 x 118	48913-HF		48713-HF	47593	1	50	813
	102 x 138	48928-HF	489280P-HF	48728-HF	47595	1	50	207

mm to inch conversions
 6.35 mm = 1/4 in
 12.7 mm = 1/2 in
 19.05 mm = 3/4 in
 25.4 mm = 1 in



Directly on suitable surfaces.
 Use the 991611 ribbon to print FLAT Polycarbonate items.

template with PET support.....page 10
 ribbonspage 11
 transparent cover CPT.....page 147

