


A comprehensive range of products designed specifically for the panel building market. Available in a standard range PVC or high performance Limited Fire Hazard (LFH) material.

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Grey RAL 7030 PVC	ORDER CODE Black PVC	ORDER CODE Blue PVC
19/50	25/54	24	10450018	0980	-
25/37.5	29/41	24	10450022	0981	-
25/50	29/54	24	10450023	0913	09136
25/75	29/80	16	10450024	0914	09146
25/100	29/105	16	10450025	0983	-
37.5/37.5	41/41	24	10450032	0984	-
37.5/50	41/54	16	10450033	0985	09856
37.5/75	41/80	16	10450034	0986	09866
37.5/100	41/105	16	10450035	0987	-
50/25	54/29	24	10450051	0988	-
50/37.5	54/41	16	10450052	0989	-
50/50	54/54	16	10450053	0916	09166
50/75	54/80	16	10450054	0917	09176
50/100	54/105	8	10450055	0992	-
75/37.5	80/41	16	10450072	0993	-
75/50	80/54	16	10450073	0994	-
75/75	80/80	16	10450074	0919	09196
75/100	80/105	8	10450075	0996	-
100/50	105/54	8	10450103	0998	-
100/75	105/80	8	10450104	0999	-
100/100	105/105	8	01450105	1000	10006
100/125	105/130	8	10450106	1001	-
125/75	130/80	8	10450124	0941	-

Note: Size 100/125 is not DIN 43659 (base slots) • Size 50/25 has 19mm slot pitching.

BETADUCT

- Open Slot
- Narrow Slot
- Closed Slot
- Plain
- LFH Betaduct
- Accessories



Open Slot Betaduct

- Supplied with lid
- Wide fingers giving additional cable support
- Terminated wires can be re-routed easily
- 20mm slot pitching
- 23 sizes, available in grey, black or blue. Other colours on request

Material

Self extinguishing PVC.

Standard Colours

RAL 7030 grey, black and blue.

Service Temperature

-15°C to +60°C.

Flammability

UL94 V-O rated material.

Standards

Base slots to DIN 43659.

Approvals

CSA, UL and Lloyds Register.