



## Parallel connectors, Cu, standard type



- ▶ For multi-stranded round conductors, e.g. to DIN EN 60228 Cl. 2
- ▶ Ideal for connecting differing cable cross-sections
- ▶ Simple cable entry due to internal chamfer

### Characteristics

- Annealed material optimises material and crimping properties

### Material

- Copper (EN13600)

### Surface


- Tin-plated to protect against corrosion

### Technical instructions

- Tool: see page 38

### Additional information

- The stated nominal cross-section corresponds to the total cross-section of the cable
- Additional conductor types and combinations on request



Nominal cross section mm <sup>2</sup>	Part No.	Dimension mm			Weight/ 100 pcs. ~ kg	Packing unit/pcs
		d1	d4	l		
1.5	<b>148R</b>	1.8	3.3	5	0.03	100
2.5	<b>149R</b>	2.3	4.2	5	0.04	100
4	<b>150R</b>	3.0	5.0	7	0.08	100
6	<b>151R</b>	4.0	6.0	7	0.09	100
10	<b>152R</b>	4.5	7.0	9	0.17	100
16	<b>153R</b>	5.5	8.5	10	0.28	100
25	<b>154R</b>	7.0	10.0	13	0.44	100
35	<b>155R</b>	8.5	12.0	16	0.78	100
50	<b>156R</b>	10.0	14.0	19	1.22	100
70	<b>157R</b>	12.0	16.5	19	1.62	50
95	<b>158R</b>	13.5	18.0	20	1.90	50
120	<b>159R</b>	15.0	19.5	22	2.28	50
150	<b>160R</b>	16.5	21.0	26	3.00	50
185	<b>161R</b>	19.0	24.0	30	4.37	50
240	<b>162R</b>	21.0	26.0	32	5.30	25
300	<b>163R</b>	23.5	29.5	36	8.05	25