


EBT-6U uncoated SS316 ball-lock ties

EBT-6U uncoated stainless steel cable ties provide a low cost solution to the electrical contractor for fixing and clamping applications.

Excellent weather, heat, corrosion, chemical and fire resistance, ensure they are suitable for indoor, outdoor and underground applications, that require high strength and reliability.

Ordering information

Part Number	Pack Qty (pcs)	Length (mm)	Width (mm)	Max Bundle Dia (mm)	Min Tensile Strength (N)
EBT-6U-046-0100	100	100	4.6	18	667
EBT-6U-046-0150	100	150	4.6	34	667
EBT-6U-046-0200	100	200	4.6	50	667
EBT-6U-046-0260	100	260	4.6	69	667
EBT-6U-046-0300	100	300	4.6	80	667
EBT-6U-046-0360	100	360	4.6	100	667
EBT-6U-046-0520	100	520	4.6	151	667
EBT-6U-046-0620	100	620	4.6	183	667
EBT-6U-046-0680	100	680	4.6	200	667
EBT-6U-046-0840	100	840	4.6	254	667
EBT-6U-046-1000	100	1000	4.6	304	667
EBT-6U-079-0100	100	100	7.9	18	1335
EBT-6U-079-0150	100	150	7.9	34	1335
EBT-6U-079-0200	100	200	7.9	50	1335
EBT-6U-079-0260	100	260	7.9	69	1335
EBT-6U-079-0300	100	300	7.9	80	1335
EBT-6U-079-0360	100	360	7.9	100	1335
EBT-6U-079-0520	100	520	7.9	151	1335
EBT-6U-079-0620	100	620	7.9	183	1335
EBT-6U-079-0680	100	680	7.9	200	1335
EBT-6U-079-0840	100	840	7.9	254	1335
EBT-6U-079-1000	100	1000	7.9	304	1335



Application tooling

EFSST

- For 4.6 & 7.9mm widths
- Lever action cuts off excess tail
- Easy grip handle design
- Installer controlled tensioning
- Suitable for coated or non-coated cable ties



ECTT2

- For 4.6 & 7.9mm widths
- Automatic cut off of excess tail
- Adjustable tensioning
- Metal body construction
- Low cost solution



Technical Data



Colour

Metallic

Material

Marine Grade SS316

Operating temperature

-60°C up to +300°C.

Features

- UL94 fireproof
- Halogen free
- UV resistant
- Rounded edges
- Rollerball locking mechanism
- 4.6 & 7.9mm wide options
- Eleven lengths

Tensile Strength

4.6mm wide = 667N

7.9mm wide = 1335N