



EFC-N Nylon PA6 Flexible Conduit



Ordering information

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
EFC-N16-050	16mm PA6 Flexible Conduit	Black	16	11	50m
EFC-N20-050	20mm PA6 Flexible Conduit	Black	20	14	50m
EFC-N25-050	25mm PA6 Flexible Conduit	Black	25	19	50m
EFC-N32-025	32mm PA6 Flexible Conduit	Black	32	26	25m
EFC-N20-CP10	20mm PA6 Contractor Pack	Black	20	14	10m
EFC-N25-CP10	25mm PA6 Contractor Pack	Black	25	19	10m
EFC-N16-SF	16mm Conduit Straight Fitting	Black			10pcs
EFC-N20-SF	20mm Conduit Straight Fitting	Black			10pcs
EFC-N25-SF	25mm Conduit Straight Fitting	Black			10pcs
EFC-N32-SF	32mm Conduit Straight Fitting	Black			10pcs
EFC-N16-RF	16mm Conduit 90° Fitting	Black			10pcs
EFC-N20-RF	20mm Conduit 90° Fitting	Black			10pcs
EFC-N25-RF	25mm Conduit 90° Fitting	Black			10pcs
EFC-N32-RF	32mm Conduit 90° Fitting	Black			10pcs

*All dimensions in mm



Contractors pack

- 10 metres of conduit
- 10 nylon glands
- 10 locknuts



Straight fitting

- 10 pieces per pack
- complete with locknut
- IP66



90° elbow fitting

- 10 pieces per pack
- complete with locknut
- IP66

Technical Data



Material Nylon PA6

Operating Temperature -40°C to +120°C

Compression Strength 60kg/100mm

IP Rating IP66

- Self extinguishing
- High impact strength
- Manufactured in the UK
- BS EN 61386 compliant
- One-piece IP66 rated fittings
- Contractor pack options

EFC-HCC Nylon PA6 Hinged Conduit Clips



Ordering information

Part number	Description	Colour		Pack Size
EFC-HCC-N16	16mm PA6 Hinged Clip	Black		10pcs
EFC-HCC-N20	20mm PA6 Hinged Clip	Black		10pcs
EFC-HCC-N25	25mm PA6 Hinged Clip	Black		10pcs
EFC-HCC-N32	32mm PA6 Hinged Clip	Black		10pcs
EFC-HCC-N20W	20mm PA6 Hinged Clip	White		10pcs
EFC-HCC-N25W	25mm PA6 Hinged Clip	White		10pcs

*All dimensions in mm

Technical Data



Material Nylon PA6

Operating Temperature -40°C to +120°C

- Fixing hole
- One piece design
- Manufactured in the UK