

PLC legends

precut

Legends replace the strips supplied with the devices and automatically print at the correct spacing.

Consult us for availability of other colours.

Note: UV resistance may vary between colours.

MG-PLC



Material: Rigid PVC, self extinguishing class V0: UL94; the colours white PVC10050WH and yellow PVC10050YE are UL approved.

Operating temperature range: -30°C (-22°F) to +60°C (+140°F)

PVC
0.3mm
SF
30°C
60°C
UL94 V0
RoHS COMPLIANT 2011/65/EU

Family	Component	Size mm	Type				Legends per sheet	Quantity	SW code
			white	yellow	Siemens green	grey			
MG-PLC	I/O Siemens SIMATIC ET 200S	12,7 x 50	71092	71042	71052	71002GY	14	140	885
	PLC Siemens SIMATIC S7 Profisafe 6ES7	25,6 x 50	71094	71044			8	80	895
	PLC Siemens SIMATIC S7-1500 KOMPAKT	12,7 x 109	71099	71049	71059	71009GY	8	80	897
	PLC Siemens SIMATIC ET 200SP	12,7 x 31	71098	71048	71058	71008GY	21	210	900
	PLC Siemens SIMATIC	52 x 80			71053		2	20	889

PVC
0.5mm
SF
30°C
60°C
UL94 V0
RoHS COMPLIANT 2011/65/EU

Family	Component	Size mm	Type				Legends per sheet	Quantity	SW code
			white PVC10050WH	yellow PVC10050YE	Siemens green	grey			
MG-PLC	PLC Siemens SIMATIC S7-300	17,5 x 103,5	71090	71040	71050	71000GY	6	60	882
		22 x 38	71097	71047			10	100	904
	PLC Siemens SIMATIC S7-1500	22,75 x 103,5	71091	71041	71051	71001GY	4	40	883
		22,75 x 109	71096	71046	71056		4	40	896

Material: Polycarbonate, Halogen Free, self extinguishing class V0: UL94.

Operating temperature range: -40°C (-40°F) to +130°C (+266°F)



PC
HF
SF
40°C
130°C
UL94 V0
RoHS COMPLIANT 2011/65/EU

Family	Component	Size mm	Type metallic grey	Thickness mm	Legends per sheet	Quantity	SW code
MG-PLC-HF	PLC Siemens SIMATIC S7-300	17,5 x 103,5	71000-HF	0,5	6	60	882
		22,75 x 103,5	71001-HF	0,5	4	40	883

Direct application to PLCs.
Use the 991611 ribbon to print FLAT Polycarbonate items



template with PET support.....page 10
ribbons.....page 11

