

# MG-TAPW



## Legends

### precut

MG-TAPW legends are used, with legend holders or legend rails, to identify a wide range of cables and components.

Consult us for availability of other colors.

Note: UV resistance may vary between colors.

**Material:** Rigid PVC, self extinguishing class V0 according to UL94; the colors white PVC10050WH and yellow PVC10050YE are UL approved.

**Operating temperature range:** -22°F to +140°F

PVC SF 22°F 140°F

UL US RoHS COMPLIANT 2011/65/EU

Family	Component	Size mm	Type				Tags per sheet	Quantity	SW code
			white PVC10050WH	yellow PVC10050YE	blue	green			
MG-TAPW	Entrelec PEAD, Wago 249-119	9 x 12	49092N	49042N			88	2,200	360
		9 x 15	49093N	49043N		49053N	77	1,925	361
		9 x 20	49090N	49040N			55	2,750	362
		9 x 29	49096	49046	49066		30	1,500	363
		9 x 35	49091N	49041N			33	1,650	364
		9 x 50	49094	49044			20	1,000	376
		9 x 70	49095N	49045N		49055N	11	550	378

mm to inch conversions  
 6.35 mm = 1/4 in  
 12.7 mm = 1/2 in  
 19.05 mm = 3/4 in  
 25.4 mm = 1 in

**Material:** Polycarbonate, Halogen Free, self extinguishing class V0 according to UL94; the color white PC10050WH is EN 45545-2 approved.

**Operating temperature range:** -40°F to +266°F

PC HF SF 40°F 266°F

EN 45545-2 RoHS COMPLIANT 2011/65/EU

Family	Size mm	Type white PC10050WH	Tags per sheet	Quantity	SW code
MG-TAPW-HF	9 x 35	49091N-HF	33	1,650	364
	9 x 50	49094-HF	20	1,000	376
	17 x 35	45194-HF	18	900	711



Use the 991611 ribbon to print FLAT Polycarbonate items  
 template with PET support ..... page 10  
 ribbons ..... page 11

legend holders PMT-AC ..... page 133  
 legend holders PMT-ET ..... page 134  
 legend holders PMT-DT ..... page 135  
 legend rails RT-TAPW ..... page 149

