


ECT nylon cable ties

ECT cable ties have internal serrations allowing for a positive hold on to cable and pipe bundles. The head design ensures a high tensile strength while allowing a very low insertion force.

These general purpose versatile fasteners can be used in countless applications and are used throughout mass transit, shipbuilding, petrochemical, automotive, construction and electrical contracting.

Ordering information

BLACK Part Number	NATURAL Part Number	Pack Qty (pcs)	Length (mm)	Width (mm)	Max Dia (mm)	Min Tensile (kg)
ECT80X2.4B	ECT80X2.4N	100	80	2.4	15	8.0
ECT100X2.5B	ECT100X2.5N	100	100	2.5	22	8.1
ECT120X2.5B	ECT120X2.5N	100	120	2.5	24	8.1
ECT165X2.5B	ECT165X2.5N	100	165	2.5	40	8.1
ECT200X2.5B	ECT200X2.5N	100	200	2.5	53	8.1
ECT140X3.6B	ECT140X3.6N	100	140	3.6	33	18.2
ECT180X3.6B	ECT180X3.6N	100	180	3.6	53	18.2
ECT200X3.6B	ECT200X3.6N	100	200	3.6	53	18.2
ECT300X3.6B	ECT300X3.6N	100	300	3.6	102	18.2
ECT120X4.8B	ECT120X4.8N	100	120	4.8	24	22.2
ECT160X4.8B	ECT160X4.8N	100	160	4.8	38	22.2
ECT200X4.8B	ECT200X4.8N	100	200	4.8	50	22.2
ECT250X4.8B	ECT250X4.8N	100	250	4.8	60	22.2
ECT300X4.8B	ECT300X4.8N	100	300	4.8	76	22.2
ECT370X4.8B	ECT370X4.8N	100	370	4.8	102	22.2
ECT430X4.8B	ECT430X4.8N	100	430	4.8	110	22.2
ECT150X7.6B	ECT150X7.6N	100	150	7.6	35	54.4
ECT200X7.6B	ECT200X7.6N	100	200	7.6	50	54.4
ECT300X7.6B	ECT300X7.6N	100	300	7.6	76	54.4
ECT370X7.6B	ECT370X7.6N	100	370	7.6	102	54.4
ECT430X9.0B	ECT430X9.0N	100	430	9.0	110	79.4
ECT530X9.0B	ECT530X9.0N	100	530	9.0	140	79.4
ECT610X9.0B	ECT610X9.0N	100	610	9.0	180	79.4
ECT710X9.0B	ECT710X9.0N	100	710	9.0	190	79.4
ECT780X9.0B	ECT780X9.0N	100	780	9.0	228	79.4
ECT914X9.0B	ECT914X9.0N	100	914	9.0	265	79.4
ECT1220X9.0B	ECT1220X9.0N	100	1220	9.0	325	79.4
ECT280X12.7B	ECT280X12.7N	100	280	12.7	70	114.0
ECT380X12.7B	ECT380X12.7N	100	380	12.7	102	114.0
ECT480X12.7B	ECT480X12.7N	100	480	12.7	120	114.0
ECT580X12.7B	ECT580X12.7N	100	580	12.7	204	114.0
ECT730X12.7B	ECT730X12.7N	100	730	12.7	190	114.0
ECT880X12.7B	ECT880X12.7N	100	880	12.7	240	114.0
ECT1030X12.7B	ECT1030X12.7N	100	1030	12.7	295	114.0



Application tooling

ECTT1

For fast, safe tensioning and cut off of excess tail
Suitable for nylon cable tie widths from 2.4 to 4.8mm
Material : Metal bodied
Colour : Red
Dimensions : 178 x 140 x 29mm



Technical Data



Colour

Black or natural

Material

Halogen free Polyamide 6.6
Nylon 66

Operating temperature

-40°C to +85°C

Dielectric Strength

50,000 Volts/mm

Compliance

BS EN50146
BE EN 62275:2009
DIN EN 62275 (VDE0604-201)
IEC 62275(2006-10)
UL Approved E474504

Features


Halogen free
UL94 V2
Fast, secure installation
High resistance to oils, greases,
oil derivatives and chloride solvents
Smooth round edges
Wide range of sizes

ECT coloured cable ties

The perfect solution for applications such as colour coding, date/year identification, asset tagging, package or area coding, and ensuring a fast and effective visual identifier on site.

Ordering information

Part Number	Colour	Pack Qty (pcs)	Length (mm)	Width (mm)	Max Dia (mm)	Min Tensile (kg)
ECT100X2.5BL	BLUE	100	100	2.5	22	8.1
ECT140X3.6BL	BLUE	100	140	3.6	33	18.2
ECT200X4.8BL	BLUE	100	200	4.8	50	22.2
ECT300X4.8BL	BLUE	100	300	4.8	76	22.2
ECT100X2.5BR	BROWN/ORANGE	100	100	2.5	22	8.1
ECT140X3.6BR	BROWN/ORANGE	100	140	3.6	33	18.2
ECT200X4.8BR	BROWN/ORANGE	100	200	4.8	50	22.2
ECT300X4.8BR	BROWN/ORANGE	100	300	4.8	76	22.2
ECT100X2.5G	GREEN	100	100	2.5	22	8.1
ECT140X3.6G	GREEN	100	140	3.6	33	18.2
ECT200X4.8G	GREEN	100	200	4.8	50	22.2
ECT300X4.8G	GREEN	100	300	4.8	76	22.2
ECT100X2.5R	RED	100	100	2.5	22	8.1
ECT140X3.6R	RED	100	140	3.6	33	18.2
ECT200X4.8R	RED	100	200	4.8	50	22.2
ECT300X4.8R	RED	100	300	4.8	76	22.2
ECT100X2.5Y	YELLOW	100	100	2.5	22	8.1
ECT140X3.6Y	YELLOW	100	140	3.6	33	18.2
ECT200X4.8Y	YELLOW	100	200	4.8	50	22.2
ECT300X4.8Y	YELLOW	100	300	4.8	76	22.2
ECT300X4.8S	SILVER	100	300	4.8	76	22.2
ECT370X4.8S	SILVER	100	370	4.8	102	22.2




ECT weather resistant cable ties

Weather resistant cable ties have a greater resistance to ultraviolet light which is known to damage natural nylon. This range can be used where adverse outdoor conditions exist.

Ordering information

Part Number	Colour	Pack Qty (pcs)	Length (mm)	Width (mm)	Max Dia (mm)	Min Tensile (kg)
ECT100X2.5WR	Black	100	100	2.5	22	8.1
ECT150X3.6WR	Black	100	150	3.6	35	18.2
ECT200X3.6WR	Black	100	200	3.6	53	18.2
ECT200X4.8WR	Black	100	200	4.8	50	22.2
ECT300X4.8WR	Black	100	300	4.8	76	22.2
ECT370X4.8WR	Black	100	370	4.8	102	22.2
ECT530X4.8WR	Black	100	530	4.8	140	22.2
ECT540X7.6WR	Black	100	540	7.6	140	54.4
ECT1220X9.0WR	Black	100	1220	9.0	365	79.4



Telephone : +44 (0)141 941 3689 Email : sales@expresselectrical.co.uk

Technical Data



Colour

Blue, Brown/Orange, Green, Red, Yellow and Silver

Material

Halogen free Polyamide 6.6 (UL approved Nylon 66)

Operating temperature

-40°C to +85°C

Features

- Halogen free
- UL94 V2
- High tensile strength
- Low insertion force
- Excellent resistance to weathering
- Fast, secure installation
- Smooth round edges
- Six colour choices



Colour

Black

Material

Halogen free Polyamide 6.6 (UV Stabilised Nylon 66)

Operating temperature

-40° to +120°C

Features

- Halogen free
- UL94 V2
- Fast, secure installation
- Smooth round edges
- High carbon content for UV resistance
- Heat Stabilised
- Suitable for indoor and outdoor use