

EFMT-3 Floor Marking Tapes

An effective and durable floor marking tape, used as an alternative to paint and resin to achieve 5S floor marking status.

Simply peel back the liner and stick down. No preparation is required and unlike paints, no fumes or solvents are emitted. The work area can remain in use whilst it is being applied.

The homogeneous construction ensures if scratched it does not affect the colour. It will not snap if removed, enabling easy floor marking changes, unlike paint or resin.



Ordering Information for EFMT-3T (Textured)

Colour	50mm (2")	75mm (3")	100mm (4")
Black	EFMT-3T-050-0	EFMT-3T-075-0	EFMT-3T-100-0
Red	EFMT-3T-050-2	EFMT-3T-075-2	EFMT-3T-100-2
Orange	EFMT-3T-050-3	EFMT-3T-075-3	EFMT-3T-100-3
Yellow	EFMT-3T-050-4	EFMT-3T-075-4	EFMT-3T-100-4
Green	EFMT-3T-050-5	EFMT-3T-075-5	EFMT-3T-100-5
Blue	EFMT-3T-050-6	EFMT-3T-075-6	EFMT-3T-100-6
White	EFMT-3T-050-9	EFMT-3T-075-9	EFMT-3T-100-9
White/Red	EFMT-3T-050-92	EFMT-3T-075-92	EFMT-3T-100-92
Yellow/Black	EFMT-3T-050-40	EFMT-3T-075-40	EFMT-3T-100-40
White/Black	EFMT-3T-050-90	EFMT-3T-075-90	EFMT-3T-100-90

Ordering Information for EFMT-3S (Smooth)

Colour	50mm (2")	75mm (3")	100mm (4")
Black	EFMT-3S-050-0	EFMT-3S-075-0	EFMT-3S-100-0
Red	EFMT-3S-050-2	EFMT-3S-075-2	EFMT-3S-100-2
Orange	EFMT-3S-050-3	EFMT-3S-075-3	EFMT-3S-100-3
Yellow	EFMT-3S-050-4	EFMT-3S-075-4	EFMT-3S-100-4
Green	EFMT-3S-050-5	EFMT-3S-075-5	EFMT-3S-100-5
Blue	EFMT-3S-050-6	EFMT-3S-075-6	EFMT-3S-100-6
White	EFMT-3S-050-9	EFMT-3S-075-9	EFMT-3S-100-9
White/Red	EFMT-3S-050-92	EFMT-3S-075-92	EFMT-3S-100-92
Yellow/Black	EFMT-3S-050-40	EFMT-3S-075-40	EFMT-3S-100-40

Technical Data



Standard Colours - Textured

Black, Red, Orange, Yellow, Green, Blue, White, White/Red, Yellow/Black and White/Black.

Standard Colours - Smooth

Black, Red, Orange, Yellow, Green, Blue, White, White/Red, Yellow/Black.

Material Composition

1mm PVC
0.2mm Adhesive
0.1mm Liner

Warranty

3 years
The warranty does not cover items being dragged, pushed or scraped across such as pallets or transit skids.

Operating Temperature

-30°C up to +700°C.

Test Results

Lloyd 500N load cell

Tensile strength, N/25mm : >200

PSTC-6

Initial tack (cm) : < 8

ASTM-D1000

180° Adhesion (kg/25.4mm) : >1.8

PSTC-7

Holding Power (hrs/kg/25.4mm²) : >48

Storage

Store in original packaging.
Recommended storage environment is +15°C to +25°C and 50% relative humidity.