

Part Number System for Pan-Wrap™

PW	50	F	—	C	20
Type	Outside Diameter	Material		Package Size	Color Suffix
PW = Pan-Wrap™	50 = 1/2" 75 = 3/4" 100 = 1" 150 = 1 1/2"	F = Polyethylene FR = Flame Retardant Polyethylene		L = 50' (15.2m) C = 100' (30.5m) T = 200' (61.0m)	Leave Blank = Natural 20 = Black 3 = Orange 4 = Yellow

Pan-Wrap™ Split Harness Wrap



- Patented slot pattern provides improved flexibility and abrasion protection in any application
- Unique wall design provides for easy cable breakouts
- Innovative design maintains uniform bundle protection in dynamic applications
- Considerably reduces installation time
- Large overlap accommodates a wide range of bundle diameters
- Packaged on a reel for easy handling and dispensing of product
- UL File: E141152
- Voltage rating: 600 V

Part Number	Material	Color	Length Per Reel		Max. Bundle Diameter		Min. Bundle Diameter‡		Temperature Range	Nominal I.D.		Std. Pkg. Qty.*
			Ft.	m	In.	mm	In.	mm		In.	mm	
PW50F-T	Polyethylene	Natural	200	61.0	0.55	14.0	0.43	10.9	-40°F – 122°F (-40°C – 50°C)	0.50	12.7	1
PW50F-T20		Black	200	61.0	0.55	14.0	0.43	10.9				
PW50F-T3		Orange	200	61.0	0.55	14.0	0.43	10.9				
PW50F-T4		Yellow	200	61.0	0.55	14.0	0.43	10.9				
PW50FR-TY	Flame Retardant Polyethylene	Natural	200	61.0	0.55	14.0	0.43	10.9	-4°F – 122°F (-20°C – 50°C)	0.50	12.7	
PW50FR-T20Y		Black	200	61.0	0.55	14.0	0.43	10.9				
PW75F-C	Polyethylene	Natural	100	30.5	0.81	20.6	0.55	14.0	-40°F – 122°F (-40°C – 50°C)	0.75	19.1	
PW75F-C20		Black	100	30.5	0.81	20.6	0.55	14.0				
PW75F-C3		Orange	100	30.5	0.81	20.6	0.55	14.0				
PW75F-C4		Yellow	100	30.5	0.81	20.6	0.55	14.0				
PW75FR-CY	Flame Retardant Polyethylene	Natural	100	30.5	0.81	20.6	0.55	14.0	-4°F – 122°F (-20°C – 50°C)	0.75	19.1	
PW75FR-C20Y		Black	100	30.5	0.81	20.6	0.55	14.0				
PW100F-C	Polyethylene	Natural	100	30.5	1.13	28.6	0.81	20.6	-40°F – 122°F (-40°C – 50°C)	1.00	25.4	
PW100F-C20		Black	100	30.5	1.13	28.6	0.81	20.6				
PW100F-C3		Orange	100	30.5	1.13	28.6	0.81	20.6				
PW100F-C4		Yellow	100	30.5	1.13	28.6	0.81	20.6				
PW100FR-CY	Flame Retardant Polyethylene	Natural	100	30.5	1.13	28.6	0.81	20.6	-4°F – 122°F (-20°C – 50°C)	1.00	25.4	
PW100FR-C20Y		Black	100	30.5	1.13	28.6	0.81	20.6				
PW150F-L	Polyethylene	Natural	50	15.2	1.63	41.3	1.13	28.6	-40°F – 122°F (-40°C – 50°C)	1.50	38.1	
PW150F-L20		Black	50	15.2	1.63	41.3	1.13	28.6				
PW150F-L3		Orange	50	15.2	1.63	41.3	1.13	28.6				
PW150F-L4		Yellow	50	15.2	1.63	41.3	1.13	28.6				
PW150FR-LY	Flame Retardant Polyethylene	Natural	50	15.2	1.63	41.3	1.13	28.6	-4°F – 122°F (-20°C – 50°C)	1.50	38.1	
PW150FR-L20Y		Black	50	15.2	1.63	41.3	1.13	28.6				

‡Diameter can be further reduced with the use of Panduit cable ties.
*Order number of reels required.