


A comprehensive range of products designed specifically for the panel building market. Available in a standard range PVC or high performance Limited Fire Hazard (LFH) material.

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Grey RAL 7030 PVC	ORDER CODE Black PVC	ORDER CODE Blue PVC
19/50	25/54	24	10450018	0980	-
25/37.5	29/41	24	10450022	0981	-
25/50	29/54	24	10450023	0913	09136
25/75	29/80	16	10450024	0914	09146
25/100	29/105	16	10450025	0983	-
37.5/37.5	41/41	24	10450032	0984	-
37.5/50	41/54	16	10450033	0985	09856
37.5/75	41/80	16	10450034	0986	09866
37.5/100	41/105	16	10450035	0987	-
50/25	54/29	24	10450051	0988	-
50/37.5	54/41	16	10450052	0989	-
50/50	54/54	16	10450053	0916	09166
50/75	54/80	16	10450054	0917	09176
50/100	54/105	8	10450055	0992	-
75/37.5	80/41	16	10450072	0993	-
75/50	80/54	16	10450073	0994	-
75/75	80/80	16	10450074	0919	09196
75/100	80/105	8	10450075	0996	-
100/50	105/54	8	10450103	0998	-
100/75	105/80	8	10450104	0999	-
100/100	105/105	8	01450105	1000	10006
100/125	105/130	8	10450106	1001	-
125/75	130/80	8	10450124	0941	-

Note: Size 100/125 is not DIN 43659 (base slots) • Size 50/25 has 19mm slot pitching.

BETADUCT

- Open Slot
- Narrow Slot
- Closed Slot
- Plain
- LFH Betaduct
- Accessories



Open Slot Betaduct

- Supplied with lid
- Wide fingers giving additional cable support
- Terminated wires can be re-routed easily
- 20mm slot pitching
- 23 sizes, available in grey, black or blue. Other colours on request

Material

Self extinguishing PVC.

Standard Colours

RAL 7030 grey, black and blue.

Service Temperature

-15°C to +60°C.

Flammability

UL94 V-O rated material.


Standards

Base slots to DIN 43659.

Approvals

CSA, UL and Lloyds Register.

Nar row Slot Betaduct



- Supplied with lid
- Ideal for use with slimmer terminal blocks where more access is required
- Improves appearance of panels with cables out in best position
- 10mm slot pitching
- 20 sizes in a choice of grey or black

Material

Self extinguishing PVC.

Standard Colours

RAL 7030 grey, black.

Service Temperature

-15°C to +60°C.

Flammability

UL94 V-O rated material.

Standards

Base slots to DIN 43659.


Approvals

CSA, UL and Lloyds Register.

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Grey RAL 7030 PVC	ORDER CODE Black PVC
19/50	25/54	24	10470018	10490018
25/37.5	29/41	24	10470022	10490022
25/50	29/54	24	10470023	10490023
25/75	29/80	16	10470024	10490024
25/100	29/105	16	10470025	10490025
37.5/37.5	41/41	24	10470032	10490032
37.5/50	41/54	16	01470033	10490033
37.7/75	41/80	16	10470034	10490034
37.5/100	41/105	16	01470035	10490035
50/37.5	54/41	16	10470052	10490052
50/50	54/54	16	10470053	10490053
50/75	54/80	16	10470054	10490054
50/100	54/105	8	10470055	10490055
75/37.5	80/41	16	10470072	10490072
75/50	80/54	16	10470073	10490073
75/75	80/80	16	10470074	10490074
75/100	80/105	8	10470075	10490075
100/50	105/54	8	10470103	10490103
100/75	105/80	8	10470104	10490104
100/100	105/105	8	10470105	10490105

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Grey RAL 7030 PVC	ORDER CODE Black PVC
15/15	17/17	48	10460011	0900
19/50	23/54	24	10460018	0950
25/20	29/25	24	10460021	0901
25/37.5	29/41	24	10460022	0951
25/50	29/54	24	10460023	0903
25/75	29/80	16	10460024	0904
25/100	29/105	16	10460025	0953
37.5/50	41/54	16	10460033	0955
37.5/75	41/80	16	10460034	0956
37.5/100	41/105	16	10460035	0975
50/25	54/29	24	10460051	0938
50/37.5	54/41	16	10460052	0959
50/50	54/54	16	10460053	0906
50/75	54/80	16	10460054	0907
50/100	54/105	8	10460055	0962
75/50	80/54	16	10460073	0964
75/75	80/80	16	10460074	0909
75/100	80/105	8	10460075	0966
100/50	105/54	8	10460103	0968
100/75	105/80	8	10460104	0969
100/125	105/130	8	10460106	0971
125/75	130/80	8	10460124	0940

Note: Sizes 15/15 and 100/125 are not DIN 43659 (base slots).
 Sizes 15/15 and 50/25 have 19mm pitching.
 Size 25/20 has 9.5mm pitching.



Closed Slot Betaduct

- Supplied with lid
- Excellent cable retention
- Enhanced protection for installers
- 20mm slot pitching
- 22 sizes, available in grey or black

Material

Self extinguishing PVC.

Standard Colours

RAL 7030 grey, black.

Service Temperature

-15°C to +60°C.

Flammability


UL94 V-O rated material.

Standards

Base slots to DIN 43659.

Approvals

CSA, UL and Lloyds Register.



Plain Betaduct

- Supplied with lid
- Ideal where no break-outs are required or side wall access is infrequent
- Complete cable protection
- 25 sizes, in either grey or black

Material

Self extinguishing PVC.

Standard Colours

RAL 7030 grey, black.

Service Temperature

-15°C to +60°C.

Flammability

UL94 V-O rated material.

Standards


Base slots to DIN 43659.

Approvals

CSA, UL and Lloyds Register.

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Grey RAL 7030 PVC	ORDER CODE Black PVC
15/15	17/17	48	10480011	0920
19/50	23/54	24	10480018	1010
25/20	29/25	24	10480021	0921
25/37.5	29/41	24	10480022	1011
25/50	29/54	24	10480023	0923
25/75	29/80	16	10480024	0924
25/100	29/105	16	10480025	1013
37.5/37.5	41/41	24	10480032	1014
37.5/50	41/54	16	10480033	1015
37.5/75	41/80	16	10480034	1016
37.5/100	41/105	16	10480035	1017
50/25	54/29	24	10480051	1018
50/37.5	54/41	16	10480052	1019
50/50	54/54	16	10480053	0926
50/75	54/80	16	10480054	0927
50/100	54/105	8	10480055	1022
75/37.5	80/41	16	10480072	1023
75/50	80/54	16	10480073	1024
75/75	80/80	16	10480074	0929
75/100	80/105	8	10480075	1026
100/50	105/54	8	10480103	1028
100/75	105/80	8	10480104	1029
100/100	105/115	8	10480105	1030
100/125	105/130	8	10480106	1031
125/75	130/80	8	10480124	0942

Note: Sizes 15/15 and 100/125 are not DIN 43659 (base slots).



LFH Betaduct

- Supplied with lid
- Choice of Open slot, Closed slot or Plain
- Limited Fire Hazard
- Zero Halogen
- Low smoke
- Wide range of sizes
- Available in black



Material

Self extinguishing. Modified PPO, Zero Halogen.

Standard Colours

Black.

Service Temperature

-30°C to +120°C.

Flammability

UL94 V-O rated material. BS476 Part 7 Class 1 (Y).

Standards

Base slots to DIN 43659.

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Open Slot LFH	ORDER CODE Closed Slot LFH	ORDER CODE Plain LFH
25/35	29/38	24	23461	23451	23471
25/50	29/54	24	23462	23452	23472
25/75	29/80	16	23463	23453	23473
50/50	54/54	16	23464	23454	23474
50/75	54/80	16	23465	23455	23475
75/75	80/80	16	23466	23456	23476

Note: Open and Closed slot have 19mm pitching.