

ESM 25 IS VDE-battery powered hydraulic cutting tool 25 mm dia.











- ▶ Housing in signal orange for simple differentiation from standard tools
- Insulated and VDE certified up to 1,000 V for increased safety when working on potentially voltage-carrying parts
- For cutting Al/St cables (ACSR), round materials (Cu, Al, St) as well as armoured cables, steel rods and stay wire
- Extremely robust design and lightweight
- ▶ All tool data in view thanks to the built-in display

Characteristics

- Choose your battery system: Bosch or Makita
- Open head, rotatable
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination

Bosch battery 18 V / 5.0 Ah, Li-lon

Makita battery 18 V / 4.0 Ah, Li-lon

Replacement blade set

- 2-stage hydraulic system with fast feed and power stroke
- Simple and safe: Automatic retraction when operation is complete
- Manual retract stop (MRS) for efficient operations
- Always ready-to-use thanks to battery charge and service display
- All data can be easily read out via Bluetooth

Suitable for

Open wires (ACSR, Aldrey), stay wire and high-tensile stay wire

Technical data				
Head type	cutter open			
Cutting range		Open wire (ACSR, Aldrey) up to dia. 25 mm, stay wire up to dia. 16 mm, hightensile stay wire up to dia. 12 mm		
Cutting force	67 kN			
Cutting cycle	depending on materia	depending on material thickness		
Charging time	15 min.			
Weight incl. battery	2.9 kg			
Ambient temperature	-10 °C up to +40 °C			
Item		Part No. Bosch	Part No. Makita	
VDE Battery powered hydraulic cutting tool 25 mm dia.		ESM25ISB	ESM25ISM	
Scope of supply				
Bosch battery 18 V / 2.0 Ah, Li-lon		RALB1EU		
Bosch quick-charger for 18 V Li-lon battery		LGLB1EU		
Makita battery 18 V / 1.5 Ah, Li-lon			RAL1	
Makita quick-charger for 18 V Li-lon battery			LGL1	
Plastic case		KKESM50IS	KKESM50IS	
Accessories				

RALB2EU

ESM25ESET

RAL2

ESM25ESET