

EFC-SR Spiral Re-inforced Flexible Conduit



Ordering information

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
EFC-SR-PVC16-030	16mm Spiral Flexible Conduit	Black	17	12	50m
EFC-SR-PVC20-030	20mm Spiral Flexible Conduit	Black	21	16	50m
EFC-SR-PVC25-030	25mm Spiral Flexible Conduit	Black	28	22	50m
EFC-SR-PVC32-030	32mm Spiral Flexible Conduit	Black	34	28	25m
EFC-SR-PVC20-CP10	20mm SR Contractor Pack	Black	21	16	10m
EFC-SR-PVC25-CP10	25mm SR Contractor Pack	Black	28	22	10m
EFC-SR-N16-SF	16mm Conduit Straight Fitting	Black			10pcs
EFC-SR-N20-SF	20mm Conduit Straight Fitting	Black			10pcs
EFC-SR-N25-SF	25mm Conduit Straight Fitting	Black			10pcs
EFC-SR-N32-SF	32mm Conduit Straight Fitting	Black			10pcs

*All dimensions in mm



Contractors pack
 - 10 metres of conduit
 - 10 nylon glands
 - 10 locknuts



Straight fitting
 - 10 pieces per pack
 - complete with locknut
 - IP66

Technical Data



Material PVC

Operating Temperature -5°C to +70°C

Compression Strength 75kg/100mm

IP Rating IP65

- Self extinguishing
- High impact strength
- Manufactured in the UK
- BS EN 61386 compliant
- IP65 rated fittings
- Contractor pack options

EPC-RS Rubber Lined Steel P-Clips



Ordering information

Part number	Description	Colour	Max Diameter	Material	Pack Size
EPC16RS4	16mm Diameter P-Clip	Self	16	SS304	25pcs
EPC25RS4	21mm Diameter P-Clip	Self	21	SS304	25pcs
EPC25RS4	25mm Diameter P-Clip	Self	25	SS304	25pcs
EPC35RS4	35mm Diameter P-Clip	Self	35	SS304	25pcs

Technical Data



Material Stainless Steel 304

Operating Temperature -40°C to +60°C

- 6.6mm fixing hole
- Fast and simple to install
- Suitable for indoor and outdoor use