

Part number

PEW 12563 PI



Flush-mounting socket outlet, PLUSO series, 2 poles + PE, 6 h (blue), 125 A, 200 ÷ 250 V, inclined

Product description

| | |
|-----------------------|--------------------------|
| Product type | Socket Flush-mounting |
| Series | PEW...PI, PLUSO |
| N. of poles | 2 poles + |
| Clock position | 6 |
| Specification | Inclined |

Technical data

| | |
|--------------------------------|-------------|
| Current | 125 A |
| Voltage | 200 ÷ 250 V |
| IP degree of protection | IP67 |

Further technical details

| | |
|---|-----------------|
| Weight | 1.230,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 5015 blue |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747070164 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|-----------------------|
| Packaging length | 335,00 mm |
| Packaging height | 320,00 mm |
| Packaging width | 400,00 mm |
| Packaging weight | 11,60 kg |
| Packaging volume | 42,88 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 8 Pcs |
| Packaging EAN code | 8015747070171 |
| Sub-packaging weight | 1,45 kg |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747070188 |

Part number

PEW 12563 PI



Catalogue drawings

(63 /125A) PEW ... PI



| PEW ... PI | A | B | C | D | E | F | G | H | I | X | Y |
|------------------|-----|-----|-----|----|----|-----|-----|----|-----|-----|-----|
| 63A 2P+⊕ | 100 | 107 | 124 | 84 | 55 | 107 | 82 | 45 | 94 | 77 | 85 |
| 3P+⊕ | 100 | 107 | 124 | 84 | 55 | 107 | 82 | 45 | 94 | 77 | 85 |
| 3P+N+⊕ | 100 | 107 | 124 | 84 | 55 | 107 | 82 | 45 | 94 | 77 | 85 |
| 125A 2P+⊕ | 130 | 130 | 143 | 94 | 87 | 119 | 102 | 56 | 112 | 104 | 104 |
| 3P+⊕ | 130 | 130 | 143 | 94 | 87 | 119 | 102 | 56 | 112 | 104 | 104 |
| 3P+N+⊕ | 130 | 130 | 143 | 94 | 87 | 119 | 102 | 56 | 112 | 104 | 104 |

Notes

Dimensions shown in mm are not binding and may be changed without notice.

- Compliant with EN 60309-1 and -2
- Enclosure, insert and spring lid in insulating, thermoplastic, self-extinguishing material
- RAL 7035 grey enclosure, spring lid colour coded according to the operating voltage
- Flange with anti-ageing gasket
- PE...PI types (IP44), spring lid
- PEW...PI types (IP67), spring lid with locking ring and gasket
- Terminals with retained screws
- 63A, 125A: with pilot contact
- Nickel-plated contacts, available on request for 16A and 32A (standard on 63A and 125A). For the code of products with nickel-plated contacts (socket holes, plug pins), add "N" to the pre-code of the corresponding standard product code; for example: PE becomes PEN and PEW becomes PEWN.
- IP44 and IP67 degrees of protection (EN 60529)