

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Grey RAL 7030 PVC	ORDER CODE Black PVC
15/15	17/17	48	10460011	0900
19/50	23/54	24	10460018	0950
25/20	29/25	24	10460021	0901
25/37.5	29/41	24	10460022	0951
25/50	29/54	24	10460023	0903
25/75	29/80	16	10460024	0904
25/100	29/105	16	10460025	0953
37.5/50	41/54	16	10460033	0955
37.5/75	41/80	16	10460034	0956
37.5/100	41/105	16	10460035	0975
50/25	54/29	24	10460051	0938
50/37.5	54/41	16	10460052	0959
50/50	54/54	16	10460053	0906
50/75	54/80	16	10460054	0907
50/100	54/105	8	10460055	0962
75/50	80/54	16	10460073	0964
75/75	80/80	16	10460074	0909
75/100	80/105	8	10460075	0966
100/50	105/54	8	10460103	0968
100/75	105/80	8	10460104	0969
100/125	105/130	8	10460106	0971
125/75	130/80	8	10460124	0940

Note: Sizes 15/15 and 100/125 are not DIN 43659 (base slots).  
 Sizes 15/15 and 50/25 have 19mm pitching.  
 Size 25/20 has 9.5mm pitching.



## Closed Slot Betaduct

- Supplied with lid
- Excellent cable retention
- Enhanced protection for installers
- 20mm slot pitching
- 22 sizes, available in grey or black

### Material

Self extinguishing PVC.

### Standard Colours

RAL 7030 grey, black.

### Service Temperature

-15°C to +60°C.

### Flammability

UL94 V-O rated material.

### Standards

Base slots to DIN 43659.

### Approvals

CSA, UL and Lloyds Register.