

EFC-LW Lightweight Nylon PA6 Flexible Conduit



Ordering information

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
EFC-LW-N10-025	10mm PA6 Flexible Conduit	Black	10	6.5	25m
EFC-LW-N12-025	12mm PA6 Flexible Conduit	Black	13	10.1	25m
EFC-LW-N16-025	16mm PA6 Flexible Conduit	Black	16	11.8	25m
EFC-LW-N18-025	18mm PA6 Flexible Conduit	Black	18.5	14.5	25m
EFC-LW-N20-025	20mm PA6 Flexible Conduit	Black	21.2	16.9	25m
EFC-LW-N25-025	25mm PA6 Flexible Conduit	Black	25.6	21.3	25m
EFC-LW-N28-025	28mm PA6 Flexible Conduit	Black	28.3	23.1	25m

*All dimensions in mm



Supplied in easy to handle 25m reels

Technical Data



Material Nylon PA6

Operating Temperature -40°C to +120°C

Compression Strength 40kg/100mm

IP Rating IP40

- Lightweight, economical range
- Impact and shock resistant
- Highly flexible
- Keep cables protected and organised

EFC-SP Nylon PA6 Split Flexible Conduit



Ordering information

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
EFC-SP-N10-025	10mm PA6 Split Conduit	Black	10	6.5	25m
EFC-SP-N12-025	12mm PA6 Split Conduit	Black	13	10.1	25m
EFC-SP-N16-025	16mm PA6 Split Conduit	Black	16	11.8	25m
EFC-SP-N18-025	18mm PA6 Split Conduit	Black	18.5	14.5	25m
EFC-SP-N20-025	20mm PA6 Split Conduit	Black	21.2	16.9	25m
EFC-SP-N25-025	25mm PA6 Split Conduit	Black	25.6	21.3	25m
EFC-SP-N28-025	28mm PA6 Split Conduit	Black	28.3	23.1	25m

*All dimensions in mm



Split conduit is supplied in easy to handle 25m reels



Ordering information - Cable insertion tools for split conduit

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
EFC-TOOL-10-18	10mm PA6 Split Conduit	Black	10	6.5	25m
EFC-TOOL-20-28	12mm PA6 Split Conduit	Black	13	10.1	25m

Technical Data



Material Nylon PA6

Operating Temperature -40°C to +120°C

Compression Strength 40kg/100mm

- Lightweight, economical range
- Highly flexible
- Split design allows easy cable entry
- Cable insertion tools available