

Nar row Slot Betaduct



- Supplied with lid
- Ideal for use with slimmer terminal blocks where more access is required
- Improves appearance of panels with cables out in best position
- 10mm slot pitching
- 20 sizes in a choice of grey or black

Material

Self extinguishing PVC.

Standard Colours

RAL 7030 grey, black.

Service Temperature

-15°C to +60°C.

Flammability

UL94 V-O rated material.

Standards

Base slots to DIN 43659.

Approvals

CSA, UL and Lloyds Register.

Nominal Size Inner (W x H) mm	Nominal Size Outer (W x H) mm	Packed (in 2m Lengths) metres	ORDER CODE Grey RAL 7030 PVC	ORDER CODE Black PVC
19/50	25/54	24	10470018	10490018
25/37.5	29/41	24	10470022	10490022
25/50	29/54	24	10470023	10490023
25/75	29/80	16	10470024	10490024
25/100	29/105	16	10470025	10490025
37.5/37.5	41/41	24	10470032	10490032
37.5/50	41/54	16	01470033	10490033
37.7/75	41/80	16	10470034	10490034
37.5/100	41/105	16	01470035	10490035
50/37.5	54/41	16	10470052	10490052
50/50	54/54	16	10470053	10490053
50/75	54/80	16	10470054	10490054
50/100	54/105	8	10470055	10490055
75/37.5	80/41	16	10470072	10490072
75/50	80/54	16	10470073	10490073
75/75	80/80	16	10470074	10490074
75/100	80/105	8	10470075	10490075
100/50	105/54	8	10470103	10490103
100/75	105/80	8	10470104	10490104
100/100	105/105	8	10470105	10490105