

EFC-PP Polypropylene Flexible Conduit



Ordering information - Black

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
EFC-PP16-100	16mm PP Flexible Conduit	Black	16	11	100m
EFC-PP20-100	20mm PP Flexible Conduit	Black	20	14	100m
EFC-PP25-050	25mm PP Flexible Conduit	Black	25	19	50m
EFC-PP32-050	32mm PP Flexible Conduit	Black	32	26	50m
EFC-PP20-CP10	20mm PP Contractor Pack	Black	20	14	10m
EFC-PP25-CP10	25mm PP Contractor Pack	Black	25	19	10m
EFC-PP20-HF	20mm Conduit Hinged Fitting	Black			10pcs
EFC-PP25-HF	25mm Conduit Hinged Fitting	Black			10pcs

*All dimensions in mm



Contractors pack

- 10 metres of conduit
- 10 polypropylene glands
- 10 locknuts



Hinged fitting

- 10 pieces per pack
- complete with locknut
- IP40

Technical Data



Material Polypropylene

Operating Temperature -20°C to +90°C

Compression Strength 35kg/100mm

IP Rating IP40

- Self extinguishing
- Acid resistant
- Manufactured in the UK
- BS EN 61386 compliant

EFC-PP Polypropylene Flexible Conduit



Ordering information - White

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
EFC-PPW20-100	20mm PP Flexible Conduit	White	20	14	100m
EFC-PPW25-050	25mm PP Flexible Conduit	White	25	19	50m
EFC-PPW20-CP10	20mm PP Contractor Pack	White	20	14	10m
EFC-PPW25-CP10	25mm PP Contractor Pack	White	25	19	10m
EFC-PPW20-HF	20mm Conduit Straight Fitting	White			10pcs
EFC-PPW25-HF	25mm Conduit Straight Fitting	White			10pcs

*All dimensions in mm



Contractors pack

- 10 metres of conduit
- 10 polypropylene glands
- 10 locknuts



Straight fitting

- 10 pieces per pack
- complete with locknut
- IP66

Technical Data



Material Polypropylene

Operating Temperature -20°C to +90°C

Compression Strength 35kg/100mm

IP Rating IP40

- Self extinguishing
- Acid resistant
- Manufactured in the UK
- BS EN 61386 compliant