

# MG-VRT-AH



## Panel plates self-adhesive with holes

### Customizable

MG-VRT-AH rigid PVC self-adhesive panel plates are used to create name plates, rating plates, data plates using company logos, technical data, serial numbers, EC certification, etc. Transparent polycarbonate covers can be used for increased durability.

Consult us for availability of other colors.

Note: UV resistance may vary between colors.

**Material:** Rigid PVC, self extinguishing class V0 according to UL94; the colors white PVC10050WH and yellow PVC10050YE are UL approved.

**Operating temperature range:** -22°F to +140°F

**Application temperature range:** +50°F to +104°F




Family	Size mm	Type						No. Holes	Tags per sheet	Quantity	SW code
		white PVC10050WH	yellow PVC10050YE	grey	red	blue	black				
MG-VRT-AH	15 x 52	88940					88140	2	14	350	831
	20 x 40	88920	88420	88720GY				2	10	250	864
	25 x 50	88906	88406					2	8	200	860
	25 x 75	88907	88407		88207			2	4	100	809
	25 x 80	88942					88142	2	4	100	832
	25 x 100	88914	88414		88214			2	4	100	206
	25 x 140	88927	88427					2	4	100	871
	29 x 140	88943					88143	2	3	75	834
	30 x 115	88967	88467					2	3	75	780
	35 x 50	88941					88141	2	6	150	833
	35 x 75	88929						2	3	75	817
	35 x 85	88944	88444					2	3	75	823
	35 x 100	88909	88409					2	3	75	818
	35 x 100	88910	88410					4	3	75	818
	35 x 142	88939						2	3	75	835
	40 x 150	88968	88468					2	2	50	781
	42 x 78	88922	88422					2	2	50	819
	50 x 100	88911	88411		88211			4	2	50	811
	50 x 140	88919				88619		4	2	50	872
	50 x 150	88956						4	2	50	843
	75 x 120	88915	88415				88115	4	1	25	816
82 x 142	88938						4	1	25	836	
102 x 138				88237	88637		4	1	25	208	
105 x 110	88912	88412	88712GY				4	1	25	859	



Directly on suitable surfaces.

template with PET support ..... page 10  
ribbons ..... page 11



## Panel plates self-adhesive with holes

### Customizable

MG-VRT-AH Polycarbonate self-adhesive panel plates are used to create name plates, rating plates, data plates using company logos, technical data, serial numbers, EC certification, etc. Transparent polycarbonate covers can be used for increased durability.

Consult us for availability of other colors.

Note: UV resistance may vary between colors.

# MG-VRT-AH



**Material:** Polycarbonate, Halogen Free, self extinguishing class V0 according to UL94

**Operating temperature range:** -40°F to +248°F

PC
HF
SF
-40°F
+248°F
RoHS COMPLIANT 2011/65/EU

Family	Size mm	Type		No. Holes	Tags per sheet	Quantity	SW code
		yellow	metallic grey				
MG-VRT-AH-HF	20 x 40		88720-HF	2	10	250	864
	50 x 100		88711-HF	4	2	50	811
	75 x 120	88415-HF	88715-HF	4	1	25	816
	105 x 110		88712-HF	4	1	25	859

mm to inch conversions  
 6.35 mm = 1/4 in  
 12.7 mm = 1/2 in  
 19.05 mm = 3/4 in  
 25.4 mm = 1 in



Directly on suitable surfaces.  
 Use the 991611 ribbon to print FLAT Polycarbonate items.

template with PET support..... page 10  
 ribbons ..... page 11

