

MG-TPMF



THERMAL TRANSFER SYSTEM FOR SHEET MEDIA

Cable tags for holders

precut 4mm push in markers, easy entry for PMF holders

SerieFLAT MG-TPMF tags are used for marking cables, conduit, tubes, conductors and components.

Presented in stem format, tags are simply snapped off their stems and inserted into the appropriate holders. Consult us for other colours.

Note: UV resistance may vary between colours.

Material: Rigid PVC, self extinguishing class V0: UL94; the colours white PVC10050WH and yellow PVC10050YE are UL approved.

Operating temperature range: -30°C (-22°F) to +60°C (+140°F)



Size mm	Type								Tags per sheet	Quantity	SW code
	white PVC10050WH	yellow PVC10050YE	grey	red	blue	violet	green	black			
4 x 10	42090B	42040B	42000BGY	42020B	42060B	42080N	42050B	42010B	112	5.600	502
4 x 12	42091B	42041B	42001BGY	42021B	42061B		42051B	42011B	80	4.000	505
4 x 15	42092B	42042B							80	4.000	503
4 x 20	42093B	42043B		42023B	42063B		42053B		64	1.600	504
4 x 30	42096B	42046B		42026B	42066B		42056B		48	1.200	509
4 x 40	42097B	42047B							32	800	508

Material: Polycarbonate, Halogen Free, self extinguishing class V0: UL94; the colours white PC10050WH and yellow PC10050YE are EN 45545-2 approved.

Operating temperature range: -40°C (-40°F) to +130°C (+266°F)



Size mm	Type					Tags per sheet	Quantity	SW code
	white PC10050WH	yellow PC10050YE	metallic grey	brown	orange			
4 x 10	42090B-HF	42040B-HF	42000B-HF	42070B-HF	42030N-HF	112	5.600	502
4 x 12	42091B-HF	42041B-HF	42001B-HF			80	4.000	505
4 x 15	42092B-HF	42042B-HF	42002B-HF			80	4.000	503
4 x 20	42093B-HF	42043B-HF				64	1.600	504
4 x 30	42096B-HF	42046B-HF				48	1.200	509
4 x 40	42097B-HF	42047B-HF				32	800	508

Use the 991611 ribbon to print FLAT Polycarbonate items.

template with PET support..... page 10

ribbons..... page 11

tag holders PMF..... page 112

tag holders PMF-AC..... page 120

tag holders PMF-ET..... page 121