

## EFC Steel Flexible Conduit

### Ordering information

Part number	Description	Colour	Outside Diameter	Inside Diameter	Pack Size
<b>EFC-BS16-030</b>	16mm Bare Steel Conduit		16.0	13.0	30m
<b>EFC-BS20-010</b>	20mm Bare Steel Conduit				20.3
<b>EFC-BS20-030</b>			30m		
<b>EFC-BS20-050</b>			50m		
<b>EFC-BS25-010</b>	25mm Bare Steel Conduit		25.0	21.1	10m
<b>EFC-BS25-030</b>					30m
<b>EFC-BS25-050</b>					50m
<b>EFC-BS32-030</b>	32mm Bare Steel Conduit		32.0	28.1	30m
<hr/>					
<b>EFC-CS16-030</b>	16mm Coated Steel Conduit		17.0	13.0	30m
<b>EFC-CS20-010</b>	20mm Coated Steel Conduit				21.5
<b>EFC-CS20-030</b>			30m		
<b>EFC-CS20-050</b>			50m		
<b>EFC-CS25-010</b>	25mm Coated Steel Conduit		26.0	21.1	10m
<b>EFC-CS25-030</b>					30m
<b>EFC-CS25-050</b>					50m
<b>EFC-CS32-030</b>	32mm Coated Steel Conduit		32.0	28.1	30m
<hr/>					
<b>EFC-BS16-FF</b>	16mm Steel Fixed Fitting	Nickel Plated Brass		10pcs	
<b>EFC-BS20-FF</b>	20mm Steel Fixed Fitting			10pcs	
<b>EFC-BS25-FF</b>	25mm Steel Fixed Fitting			10pcs	
<b>EFC-BS32-FF</b>	32mm Steel Fixed Fitting			2pcs	
<hr/>					
<b>EFC-BS16-SF</b>	16mm Steel Swivel Fitting	Nickel Plated Brass		10pcs	
<b>EFC-BS20-SF</b>	20mm Steel Swivel Fitting			10pcs	
<b>EFC-BS25-SF</b>	25mm Steel Swivel Fitting			10pcs	
<b>EFC-BS32-SF</b>	32mm Steel Swivel Fitting			2pcs	
<hr/>					
<b>EFC-BS16-LN</b>	16mm Locknut	Self Coloured Locknut		10pcs	
<b>EFC-BS20-LN</b>	20mm Locknut			10pcs	
<b>EFC-BS25-LN</b>	25mm Locknut			10pcs	
<b>EFC-BS32-LN</b>	32mm Locknut			2pcs	

\*All dimensions in mm



## Technical Data



**Material** Galvanised Steel  
**Operating Temperature** -100°C to +300°C  
**IP Rating** IP40

**Material** PVC Coated Galvanised Steel  
**Operating Temperature** -15°C to +70°C  
**IP Rating** IP54

### • Bend Radius

M16 - 40mm  
M20 - 45mm  
M25 - 55mm  
M32 - 70mm

- High mechanical strength
- Highly flexible
- Manufactured in the UK
- BS EN 61386 compliant

## EPC-RS Rubber Lined Steel P-Clips

### Ordering information

Part number	Description	Colour	Max Diameter	Material	Pack Size
<b>EPC16RS4</b>	16mm Diameter P-Clip	Self	16	SS304	25pcs
<b>EPC21RS4</b>	21mm Diameter P-Clip	Self	21	SS304	25pcs
<b>EPC25RS4</b>	25mm Diameter P-Clip	Self	25	SS304	25pcs
<b>EPC35RS4</b>	35mm Diameter P-Clip	Self	35	SS304	25pcs



## Technical Data



**Material** Stainless Steel 304

**Operating Temperature** -40°C to +60°C

- 6.6mm fixing hole
- Fast and simple to install
- Suitable for indoor and outdoor use