

MG-SIGNS

Panel legends

precut

The MG-SIGNS legends is used for in-house production of warning, hazard, prohibition and mandatory signs from pictogram provided in the library of GENIUSPRO software.

A highly versatile system for rapidly and accurately producing signs in all languages, on a one-off basis if required.



Material: Rigid PVC, self extinguishing class V0: according to UL94; the colour white PVC10050WH is UL approved.

Operating temperature range: -30°C to +60°C

Application temperature range: +10°C to +40°C



Family	Shape	Self adhesive	Size mm	Type			Ø mm Holes	Tags per sheet	Quantity	SW code		
				white PVC10050WH	yellow	red						
MG-SIGNS-R			40		991120			4	200	243		
			37 x 74	991052	991125	990987		2	100	271		
			52 x 105		991126			2	100	272		
				Ø 62	991050			22.5	2	50	252	
						991121			22,5	2	50	252
						991122			30	2	50	265
						991051			22.5	1	50	263
					Ø 90		991123		22,5	1	50	263
						991124		30,5	1	50	264	
MG-SIGNS-A		✓	40		991141			4	200	243		
		✓	100		991142			1	50	262		
		✓	Ø 40	990927	991140	990858		4	200	250		
		✓	Ø 100	990705				1	50	253		
		✓	37 x 74		991143	990986		2	100	271		
		✓	40 x 80		991144			3	75	274		
	✓	52 x 105		991145			2	100	272			



Directly on suitable surfaces.

template with PET support..... page 12
 ribbons page 13



MG-SIGNS

Panel labels

self adhesive, pre-cut

The MG-SIGNS labels is used for in-house production of warning, hazard, prohibition and mandatory signs from pictogram provided in the library of GENIUSPRO software.

A highly versatile system for rapidly and accurately producing signs in all languages, on a one-off basis if required.



Material: PVC film; the colour white PVC99008WH is UL approved.

Operating temperature range: -30°C to +70°C

Application temperature range: +10°C to +40°C



Family	Shape	Size mm	Type			Ø mm Holes	Labels per sheet	Quantity	SW code
			white PVC99008WH	yellow	red				
MG-SIGNS-VY		50		991103			4	200	241
		100		991105			1	50	242
		50		991104			4	200	260
		Ø 25	990860	990101	990992		12	600	236
		Ø 100	990702	991102			1	50	238
		37 x 74		991109	990988		2	100	246
		52 x 105	990825	991110			2	100	247
		62		991106		22,5	1	50	232
		90		991107		22,5	1	50	233
		90		991108		30,5	1	50	234
	45 x 150	990991				2	100	275	



MG-SIGNS

Panel labels

self adhesive, pre-cut

The MG-SIGNS labels is used for in-house production of warning, hazard, prohibition and mandatory signs from pictogram provided in the library of GENIUSPRO software.

A highly versatile system for rapidly and accurately producing signs in all languages, on a one-off basis if required.



Material: Polyester film; the colour metallic grey PET99005GY and the base material PETSIGNWHTR are UL approved.

Operating temperature range: -40°C to +130°C

Application temperature range: +10°C to +40°C



Family	Shape	Size mm	Type		Ø mm Holes	Labels per sheet	Quantity	SW code
			white/orange PETSIGNWHTR	metallic grey PET99005GY				
MG-SIGNS-PY		46 x 46		47826	24	4	200	230
		80 x 100	991057			1	50	276
		105 x 140	991058			1	50	277

